



# Turbulent flow over random sphere packs – kinetic energy budgets

# S. v.Wenczowski<sup>1</sup><sup>10</sup> and M. Manhart<sup>1</sup><sup>10</sup>

<sup>1</sup>Professorship of Hydromechanics, Technical University of Munich, Arcisstr. 21, 80333 Munich, Germany **Corresponding author:** M. Manhart, michael.manhart@tum.de

(Received 5 September 2024; revised 17 February 2025; accepted 13 May 2025)

Based on data from pore-resolved direct numerical simulation of turbulent flow over mono-disperse random sphere packs, we evaluate the budgets of the double-averaged turbulent kinetic energy (TKE) and the wake kinetic energy (WKE). While TKE results from temporal velocity fluctuations, WKE describes the kinetic energy in spatial variations of the time-averaged flow field. We analyse eight cases which represent sampling points within a parameter space spanned by friction Reynolds numbers  $Re_{\tau} \in [150, 500]$  and permeability Reynolds numbers  $Re_K \in [0.4, 2.8]$ . A systematic exploration of the parameter space is possible by varying the ratio between flow depth and sphere diameter  $h/D \in$  $\{3, 5, 10\}$ . With roughness Reynolds numbers of  $k_s^+ \in [20, 200]$ , the simulated cases lie within the transitionally or fully rough regime. Revisiting the budget equations, we identify a WKE production mechanism via viscous interaction of the flow field with solid surfaces. The scaling behaviour of different processes over  $Re_K$  and  $Re_\tau$  suggests that this previously unexplored mechanism has a non-negligible contribution to the WKE production. With increasing  $Re_K$ , progressively more WKE is transferred into TKE by wake production. A near-interface peak in the TKE production, however, primarily results from shear production and scales with interface-related scales. Conversely, further above the sediment bed, the TKE budget terms of cases with comparable  $Re_{\tau}$  show similarity under outerscaling. Most transport processes relocate energy in the near-interface region, whereas pressure diffusion propagates TKE and WKE into deeper regions of the sphere pack.

Key words: turbulent boundary layers, porous media, turbulence simulation

# 1. Introduction

Exchange of mass and momentum across the interface between a porous medium and a free turbulent flow occurs in a variety of natural and industrial systems. One prominent

© The Author(s), 2025. Published by Cambridge University Press. This is an Open Access article, distributed under the terms of the Creative Commons Attribution-ShareAlike licence (https://creative commons.org/licenses/by-sa/4.0), which permits re-use, distribution, and reproduction in any medium, provided the same Creative Commons licence is used to distribute the re-used or adapted article and the original article is properly cited.

#### S. v. Wenczowski and M. Manhart

example is the hyporheic zone, which comprises the uppermost sediment layers of a river bed, where the water in the pore space is in permanent bidirectional interaction with the overlying turbulent flow (e.g. Boano *et al.* 2014). The hyporheic zone is characterised by a high biogeochemical activity, which makes hyporheic exchange processes highly relevant for the health of the benthic, but also the whole aquatic ecosystem (e.g. Brunke & Gonser 1997; Battin *et al.* 2016). It is therefore of interdisciplinary interest to advance the understanding of the hydrodynamics near the interface between the turbulent flow and the granular, porous sediment bed.

Besides molecular diffusion, turbulent and dispersive transport can contribute to the hyporheic exchange (e.g. Voermans, Ghisalberti & Ivey 2018). Turbulent transport depends on temporal fluctuations in the flow field. According to Grant *et al.* (2020), those velocity fluctuations can either be induced by pressure fluctuations at the bed surface, which themselves result from turbulence in the free flow region, or can be the results of turbulent eddies entraining into the pore space. Dispersive transport, on the other hand, is associated with spatial variations in the time-averaged hyporheic flow field. Shen, Yuan & Phanikumar (2022) reported that even grain-scale inhomogeneities in the sediment bed surface can induce locally upwelling or downwelling fluid motion. A strong correlation between spatial variations of the time-averaged near-interface pressure field and the bed-normal time-averaged flow field is consistent with the concept of 'pumping', which was originally proposed by Elliott & Brooks (1997) for flow over regularly shaped macroscopic bed forms.

The analysis of the unsteady and strongly three-dimensional hyporheic flow field requires an appropriate framework. A possible approach is provided by a double-averaging technique in both time and space. First, an arbitrary flow quantity is Reynolds decomposed into a temporal mean and a temporal fluctuation. Subsequently, the temporal mean quantity is spatially averaged within a horizontal plane, which yields the double-averaged quantity and a spatial variation of the mean quantity. Initially, this method of horizontal averaging, also denoted as plane-averaging, was developed in the context of atmospheric flow problems (e.g. Wilson & Shaw 1977; Raupach & Shaw 1982). Later, the horizontal averaging method was adapted for the analysis of hyporheic flow problems, where drastic changes in porosity need to be taken into account (e.g. Giménez-Curto & Lera 1996; Nikora et al. 2001; Mignot, Barthelemy & Hurther 2009). To investigate both temporal velocity fluctuations and spatial velocity variations, as well as the interactions thereof, the horizontal averaging framework can be used to conduct a triple-decomposition of the complete kinetic energy (KE) of the flow field (e.g. Raupach & Shaw 1982; Yuan & Piomelli 2014; Ghodke & Apte 2016). Within the double-averaging framework, the mean kinetic energy (MKE) represents the kinetic energy in the temporally and spatially doubleaveraged flow field. The kinetic energy in the spatial velocity variations is referred to as wake kinetic energy, or short WKE (e.g. Finnigan 2000; Yuan & Piomelli 2014; Ghodke & Apte 2016). The remaining third part is the spatially averaged turbulent kinetic energy (TKE), which represents the temporal fluctuations in the velocity field.

Ghodke & Apte (2018) illustrate the energy transfer pathways between the different components of the total kinetic energy. The mechanisms behind the energy transfer pathways are identified via terms which appear with opposite signs in the budget equations of MKE, WKE and TKE (Yuan & Piomelli 2014). Accordingly, two different mechanisms exist, which can generate spatial variations in the mean flow field. A transfer of MKE into WKE happens when dispersive shear stresses act against the vertical gradient of the double-averaged flow field. Also the work of the double-averaged flow field against the pressure drag generates WKE at the expense of MKE. As stated by Finnigan (2000), TKE can also be produced via two different pathways. The shear production mechanism

transfers MKE into TKE when Reynolds shear stresses act against the vertical gradient of the double-averaged flow field. Besides that, form-induced production can convert WKE into TKE when the local Reynolds stresses act against local gradients introduced by velocity variations. Whereas shear production can introduce TKE on large scales, form-induced production generates TKE on the usually smaller scale of the flow obstacles, which thus 'bypasses' (Finnigan 2000) or 'short-circuits' (Raupach, Antonia & Rajagopalan 1991) the energy cascade.

Mignot et al. (2009) conducted experimental measurements in turbulent flow over gravel beds. They report that TKE production exceeds the dissipation in the form-induced layer, which comprises the region near the crests of the roughness elements. In this context, shear production plays a dominant role, whereas form-induced production was found to be negligible. Below the roughness crests, turbulent transport relocates TKE into deeper regions of the sediment bed. In contrast, an upward TKE transport was observed above the crests, which agrees with findings for rough impermeable walls (e.g. Raupach *et al.* 1991; Antonia & Krogstad 2001; Schultz & Flack 2005). At approximately twice the height of the roughness crests, Mignot *et al.* (2009) document the presence of an equilibrium layer, as described by Townsend (1961). TKE budgets in flow over porous media were also reported by several numerical studies (e.g. Breugem, Boersma & Uittenbogaard 2006; Han, He & Fang 2017; Fang et al. 2018; Wang et al. 2021). By means of pore-resolved direct numerical simulation (DNS), Shen, Yuan & Phanikumar (2020) investigated turbulent open-channel channel flow over sediment beds with both regular and random sphere arrangement in the interface region. In contrast to Mignot et al. (2009), they observe a non-negligible impact of form-induced production, which however strongly depends on the interface structure and can even change its sign. Further, Shen et al. (2020) report that the randomly structured sediment-water interface enhances the form-induced vertical TKE transport, which counteracts the other transport processes. Also Fang et al. (2018) document a significant form-induced production, which can even exceed 10 % of the shear production.

In contrast to the temporal velocity fluctuations, Ghodke & Apte (2018) remark that only few other studies (e.g. Yuan & Piomelli 2014; Ghodke & Apte 2016) systematically investigate the production, transport and destruction of spatial variations in the horizontally averaged velocity field. Using the equations derived by Raupach & Shaw (1982) under consideration of the varying porosity, Yuan & Piomelli (2014) evaluate the budget of WKE for the flow over transitionally and fully rough impermeable walls. The work of the horizontally double-averaged flow against the pressure drag is found to contribute significantly to the production of variation in the streamwise velocity field. Yuan & Piomelli (2014) documented that, with increasing roughness, larger shares of the WKE are transferred into TKE instead of being dissipated, which they explain with a clearer separation between roughness length scales and the viscous length scale. The energy transfer from WKE to the wall-normal and spanwise Reynolds normal stresses was connected to a higher isotropy of the Reynolds stress tensor. In the context of a time-volume double-averaging framework, Pinson et al. (2006) describe a kinetic energy transfer between macro-scale and sub-filter mean kinetic energy, which corresponds to a transfer from MKE to WKE. This kinetic energy transfer results from the work of the timeand volume-averaged velocity field against the time-averaged drag. Kuwata & Suga (2015) and Kuwata & Suga (2016) represent the same mechanism by a drag force term, which was found to contribute largely to the spatial variance in the flow field. It appears worthwhile to remark that the drag also includes a viscous component, which is not considered by Raupach & Shaw (1982), Yuan & Piomelli (2014) or Ghodke & Apte (2018).

The permeability Reynolds number  $Re_K = u_\tau \sqrt{K}/\nu$  and the roughness Reynolds number  $Re_{k_s} = u_\tau k_s / \nu = k_s^+$  are commonly used parameters, as the permeability K and the equivalent sand-grain roughness height  $k_s$  characterise the sediment bed. The parameters  $Re_K$  and  $k_s^+$  are connected via the sediment bed structure, such that the effects of roughness and permeability are tightly coupled for granular porous media with a narrow grain size distribution (e.g. Voermans, Ghisalberti & Ivey 2017; Shen et al. 2020; Karra et al. 2023). The roughness Reynolds number  $k_s^+$  allows a distinction between the dynamically smooth regime  $(k_s^+ < 5)$ , the transitionally rough regime and the fully rough regime  $(k_s^+ > 70)$  (Raupach *et al.* 1991; Jiménez 2004; Kadivar, Tormey & McGranaghan 2021). In the smooth regime, mainly viscous stresses transfer momentum from the flow to the solid surface, whereas pressure drag on the solid surfaces gains importance with increasing  $k_s^+$ . The permeability Reynolds number  $Re_K$  describes the permeability regime, as  $\sqrt{K}$  can be interpreted as an effective pore diameter (Breugem et al. 2006; Manes, Poggi & Ridolfi 2011; Voermans et al. 2017; Karra et al. 2023). According to the hydrodynamic framework of Voermans et al. (2017), large values of  $Re_K \gg 1$  indicate highly permeable boundaries, whereas low values ( $Re_K \ll 1$ ) are associated with effectively impermeably boundaries. A transition between both extremes takes place in the range of  $Re_K \approx 1-2$ . High permeability, paired with roughness, relaxes the wall-blocking effect and reduces the near-interface shear intensity, which affects the structure of turbulence and the composition of the turbulent kinetic energy (e.g. Breugem et al. 2006; Rosti, Cortelezzi & Quadrio 2015; Suga, Nakagawa & Kaneda 2017).

This overview indicates that the treatment of viscous effects may have received less attention within the horizontal averaging framework, which is likely due to the origins of the framework in atmospheric sciences. However, the same may not be justified for granular porous media in aquatic environments, where the flow is characterised by comparatively low permeability Reynolds numbers. Whilst several studies have evaluated the TKE budget near the sediment–water interface, the WKE budget has hardly been discussed for turbulent flow over porous granular beds. Due to the critical role of spatial velocity variations for hyporheic exchange, we feel that an evaluation of this budget could advance our current understanding. To our knowledge, also the scaling of different WKE and TKE budget terms over a wider parameter space covering both transitionally and fully rough regimes has not yet been documented.

Building on v.Wenczowski & Manhart (2024), the present study aims to answer the following questions: (i) which role(s) can viscous effects play for the spatial variations in the velocity field?; (ii) how do the different production mechanisms of TKE and WKE scale with  $Re_K$  and  $Re_{\tau}$ , and at what height do they reach their peak values?; (iii) which transport mechanisms are most efficient in relocating TKE and WKE in the near-interface region? To address these question, we revisit the budget equations for MKE, WKE and TKE in § 2. The applied methods as well as the sampled parameter space with systematically varying  $Re_{\tau}$  and  $Re_K$  are introduced in § 3. In § 4, we evaluate the TKE and WKE budgets based on datasets obtained from pore-resolved DNS, while we also shed a light on the scaling behaviour of different terms. The main results are then discussed in § 5, before § 6 concludes the study.

#### 2. Theory

The governing equations are introduced in § 2.1, and important properties of the horizontal averaging framework are outlined in § 2.2. Based on the decomposition of the kinetic

energy in § 2.3, we discuss the budgets of TKE, WKE and MKE in §§ 2.4, 2.5 and 2.6, respectively. Transfer mechanisms between the kinetic energy components are summarised in § 2.7.

#### 2.1. Governing equations

The incompressible Navier–Stokes equations for a Newtonian fluid with a density  $\rho$  and a kinematic viscosity  $\nu$  provide the basis for the budget formulations. The Einstein summation convention allows to express the conservation of mass and momentum as follows:

$$\frac{\partial u_i}{\partial x_i} = 0, \tag{2.1}$$

$$\frac{\partial u_i}{\partial t} + u_j \frac{\partial u_i}{\partial x_j} = -\frac{1}{\rho} \frac{\partial p}{\partial x_i} + v \frac{\partial^2 u_i}{\partial x_j \partial x_j} + g_i.$$
(2.2)

The coordinates are defined such that  $x_1 \equiv x$ ,  $x_2 \equiv y$  and  $x_3 \equiv z$  represent the streamwise, spanwise and bed-normal coordinate, respectively. The corresponding flow velocities are  $u_1 \equiv u$ ,  $u_2 \equiv v$  and  $u_3 \equiv w$ . The variable *p* represents the pressure and  $g_i$  is a volume force acting on the fluid. In (2.2), we express the viscous term as  $v \frac{\partial^2 u_i}{\partial x_j \partial x_j}$ , which is possible due to the solenoidality constraint imposed by (2.1). In the derivation of the budgets, this formulation will lead us to a pseudo-dissipation formulation (e.g. Pope 2000). We accept the pseudo-dissipation formulation, as it abbreviates the notation and facilitates the comparison to other studies (e.g. Finnigan 2000; Yuan & Piomelli 2014; Ghodke & Apte 2018; Hantsis & Piomelli 2020; Shen *et al.* 2020), which similarly use this formulation. In Appendix A, we show that only minor differences between full-dissipation and pseudo-dissipation are to be expected for the budgets that are evaluated in this study.

#### 2.2. Analysis framework

To analyse the flow field, we use horizontal averaging within x-y-planes, which are parallel to the mean sediment bed surface. In a first step, the Reynolds decomposition splits an arbitrary quantity  $\phi$  into an ensemble average  $\overline{\phi}$  and a temporal fluctuation  $\phi'$ :

$$\phi_{(\mathbf{x},t)} = \overline{\phi}_{(\mathbf{x})} + \phi'_{(\mathbf{x},t)}, \qquad \text{where} \qquad \overline{\phi}_{(\mathbf{x})} = \frac{1}{T} \int_0^T \phi_{(\mathbf{x},t)} \, \mathrm{d}t. \tag{2.3}$$

In a second step, the time-averaged quantity  $\overline{\phi}$  from (2.3) undergoes a decomposition with respect to space. The intrinsic average within a horizontal plane is denoted as  $\langle \overline{\phi} \rangle$ , whereas deviations from the in-plane average are marked by a tilde:

$$\overline{\phi}_{(\mathbf{x})} = \langle \overline{\phi} \rangle_{(z)} + \widetilde{\overline{\phi}}_{(\mathbf{x})}, \quad \text{where} \quad \langle \overline{\phi} \rangle_{(z)} = \frac{1}{A_f} \iint_{A_f} \overline{\phi}_{(\mathbf{x})} \, \mathrm{d}x \, \mathrm{d}y. \quad (2.4)$$

According to its definition in (2.4), the intrinsic average  $\langle \overline{\phi} \rangle$  represents an average over the fluid-filled area  $A_f$ . The superficial average  $\langle \overline{\phi} \rangle^s$ , however, refers to an average over the complete base area  $A_0$  of the averaging plane. Therefore, the in-plane porosity  $\theta(z)$  allows a transformation between intrinsic and superficial spatial averages:

$$\langle \overline{\phi} \rangle^s(z) = \theta(z) \langle \overline{\phi} \rangle(z)$$
 with  $\theta(z) = A_f(z) / A_0.$  (2.5)

It is worthwhile to note that, in contrast to  $\overline{\phi}$  and  $\phi'$ , the individual quantities  $\langle \overline{\phi} \rangle$  and  $\overline{\phi}$  do not satisfy the physical boundary conditions. In particular, the infringement of no-slip conditions on solid surfaces will give rise to terms that may appear artificial at first glance, but still allow a physical interpretation. Another consequence is that spatial derivatives and

# S. v. Wenczowski and M. Manhart

horizontal averaging operations do not commute below the crests of the sediment grains, where the area  $A_f$  changes over z. Consistent with Giménez-Curto & Lera (1996), the horizontally averaged spatial gradient of  $\overline{\phi}$  can be formulated as follows:

$$\langle \nabla \overline{\phi} \rangle = \begin{pmatrix} \left\langle \frac{\partial \overline{\phi}}{\partial x} \right\rangle \\ \left\langle \frac{\partial \overline{\phi}}{\partial y} \right\rangle \\ \left\langle \frac{\partial \overline{\phi}}{\partial z} \right\rangle \end{pmatrix} = \begin{pmatrix} \frac{1}{A_f} \oint_s \overline{\phi} \frac{n_x}{\sqrt{n_x^2 + n_y^2}} \, \mathrm{d}s \\ \frac{1}{A_f} \oint_s \overline{\phi} \frac{n_y}{\sqrt{n_x^2 + n_y^2}} \, \mathrm{d}s \\ \frac{1}{A_f} \oint_s \overline{\phi} \frac{n_y}{\sqrt{n_x^2 + n_y^2}} \, \mathrm{d}s \\ \frac{1}{\theta} \frac{\partial \theta \left\langle \overline{\phi} \right\rangle}{\partial z} + \frac{1}{A_f} \oint_s \overline{\phi} \frac{n_z}{\sqrt{n_x^2 + n_y^2}} \, \mathrm{d}s \end{pmatrix} \triangleq \begin{pmatrix} BT_1(\overline{\phi}) \\ BT_2(\overline{\phi}) \\ \frac{1}{\theta} \frac{\partial \theta \left\langle \overline{\phi} \right\rangle}{\partial z} + BT_3(\overline{\phi}) \end{pmatrix}.$$

$$(2.6)$$

The curve *s* in (2.6) describes the intersection of the averaging plane with the fluid–solid interface, e.g. the surface of sediment grains. The unit normal vector  $\mathbf{n} = (n_x, n_y, n_z)^T$  at the solid–fluid interface points out of the fluid-filled volume. To shorten the notation, we refer to the curve integrals as the boundary term, abbreviated as  $BT_i(\overline{\phi})$ .

The double-averaged momentum equation is obtained by applying the above rules to (2.2). In preview of the application, we imply that  $\langle \overline{w} \rangle = 0$ , which means that no net flux in the bed-normal direction exists, while no-slip boundary conditions apply on the surfaces of the sediment grains, such that

$$\frac{\partial \langle \overline{u} \rangle}{\partial t} = \frac{1}{\theta} \frac{\partial}{\partial z} \left( \underbrace{\theta \left( v \frac{\partial \overline{u}}{\partial z} \right)}_{visc.} - \underbrace{\theta \left( \overline{u'w'} \right)}_{turb.} - \underbrace{\theta \left( \overline{\widetilde{u}} \, \overline{\widetilde{w}} \right)}_{disp.} \right) + \underbrace{\frac{1}{\rho} BT_1(-\overline{p})}_{f_{p,i}} + \underbrace{BT_j \left( v \frac{\partial \overline{u}}{\partial x_j} \right)}_{f_{v,i}} + \langle \overline{g}_x \rangle = 0.$$
(2.7)

The time derivative of the double-averaged velocity on the left-hand side is obtained from double-averaging of the time derivative of u as the operators commute (Pope 2000, § 3.6). In statistically stationary flows, the time derivatives of double-averaged quantities are zero. Equation (2.7) shows that viscous, turbulent and dispersive stresses can transfer momentum within the fluid volume. Due to their origin, dispersive stresses are also synonymously called form-induced stresses (Giménez-Curto & Lera 1996; Nikora *et al.* 2001). Pressure drag  $f_p$  and viscous drag  $f_v$  result from pressure or viscous forces, respectively, acting on solid surfaces, e.g. of the sediment grains. Thus, they represent the momentum exchange with the fluid–solid interface. A volume force in the streamwise direction is denoted as  $g_x$ . While the interpretation of pressure drag and viscous drag as boundary terms is decisive for the further derivations, the equalities in (2.6) allow us to evaluate  $f_p$  and  $f_v$  from plane averages within an x-y-periodic domain. In Appendix B, we demonstrate that an evaluation as plane-averages is advantageous for an immersed boundary representation, while good agreement with values obtained from an actual surface integration is observed.

# Journal of Fluid Mechanics

# 2.3. Decomposition of the kinetic energy

The horizontal averaging framework allows a decomposition of the double-averaged total kinetic energy into three components:

$$\underbrace{\left(\frac{1}{2}\overline{u_{j}u_{j}}\right)}_{\text{KE}} = \underbrace{\left(\frac{1}{2}\overline{u_{j}'u_{j}'}\right)}_{(\text{TKE})} + \underbrace{\left(\frac{1}{2}\widetilde{\overline{u}_{j}}\widetilde{\overline{u}_{j}}\right)}_{(\text{WKE})} + \underbrace{\frac{1}{2}\langle\overline{u}_{j}\rangle\langle\overline{u}_{j}\rangle}_{\text{MKE}}.$$
(2.8)

To be consistent with the nomenclature of Finnigan (2000), Yuan & Piomelli (2014) and Ghodke & Apte (2016), we will use the terms turbulent kinetic energy (TKE), wake kinetic energy (WKE) and mean kinetic energy (MKE) to distinguish the three terms on the righthand side of (2.8). Together, WKE and MKE constitute the energy in the time-averaged mean flow field. The total WKE and total TKE result from the sum of all dispersive or Reynolds normal stresses, respectively. In the following, budget expressions for the total energies as well as for individual components will be presented. Like in (2.7), the time derivative of the double-averaged kinetic energies is zero in a statistically stationary flow. By checking the closure of the budget, we can assess if sufficient statistics have been sampled.

#### 2.4. Budget equation for the TKE components

Without a summation over the Greek index  $\alpha = 1, 2, 3, (2.9)$  formulates a budget for the horizontally averaged individual TKE components, which are interconnected via an intercomponent redistribution term. When summed over  $\alpha$ , the budget for the horizontally averaged TKE is obtained via

$$\frac{\partial}{\partial t} \left\langle \frac{1}{2} \overline{u'_{\alpha} u'_{\alpha}} \right\rangle = \underbrace{-\left\langle \overline{u'_{\alpha} u'_{j}} \right\rangle}_{\text{production}(\Pi_{shear} + \Pi_{wake} + \Pi_{mean})} - \left\langle \overline{u'_{\alpha} u'_{j}} \right\rangle \left\langle \frac{\partial}{\partial x_{j}} \right\rangle \\
\underbrace{-\frac{1}{2} \frac{1}{\theta}}_{\text{production}(\Pi_{shear} + \Pi_{wake} + \Pi_{mean})}_{\text{transport}(T_{disp}} - \frac{1}{2} \frac{1}{\theta} \frac{\partial \theta \left\langle \overline{u'_{\alpha} u'_{\alpha}} \right\rangle}_{\partial x_{j}} - \frac{1}{2} \frac{1}{\theta} \frac{\partial \theta \left\langle \overline{u'_{\alpha} u'_{\alpha} u'_{\alpha}} \right\rangle}_{\partial x_{j}} + \frac{1}{2} \frac{1}{\theta} \frac{\partial \theta \left\langle v \frac{\partial \overline{u'_{\alpha} u'_{\alpha}}}{\partial x_{j}} \right\rangle}_{\text{transport}(T_{disp} + T_{turb} + T_{visc})} \\
\underbrace{-\frac{1}{\rho} \frac{1}{\theta} \frac{\partial \theta \left\langle \overline{p' u'_{\alpha}} \right\rangle}_{\text{transport}(T_{pres})}}_{\text{transport}(R)} \underbrace{+\frac{1}{\rho} \left\langle \overline{p' \frac{\partial u'_{\alpha}}{\partial x_{\alpha}}} \right\rangle}_{\text{redistribution}(R)} \underbrace{-v \left\langle \frac{\partial u'_{\alpha} \frac{\partial u'_{\alpha}}{\partial x_{j}} \right\rangle}_{\text{(pseudo-)dissipation}(\epsilon)} = 0. \quad (2.9)$$

The first three terms on the right-hand side together represent the total plane-averaged TKE production. The fourth to seventh terms are responsible for dispersive transport, turbulent transport, diffusive transport and pressure transport in the bed-normal direction. The eighth term represents the pressure-based inter-component redistribution of TKE, which can act as a sink or source in the component-wise budgets, whereas it has zero-value in the complete TKE budget. Finally, the ninth term represents the dissipation of TKE in a pseudo-dissipation formulation (Pope 2000). The horizontal averaging framework allows a further decomposition of the TKE production. Accordingly, the first production term in (2.9) is referred to as shear production and would account for the complete production in smooth-wall channel flow. The second and third terms are commonly named wake production and mean production, respectively (e.g. Mignot *et al.* 2009). The mean

# S. v. Wenczowski and M. Manhart

production is tightly linked to porosity changes via  $\langle \partial \tilde{u}_{\alpha} / \partial x_j \rangle = BT_j(\tilde{u}_{\alpha}) = \langle \bar{u}_{\alpha} \rangle \partial \theta / \partial z$ , which makes a physical interpretation of the individual term difficult. Therefore, we summarise wake production and mean production in the form-induced production  $\Pi_{form}$ , i.e.

$$\Pi_{form} = -\left\langle \overline{u'_{\alpha}u'_{j}} \; \frac{\partial \; \widetilde{\overline{u}}_{\alpha}}{\partial x_{j}} \right\rangle = \Pi_{wake} + \Pi_{mean}. \tag{2.10}$$

As shown by (2.10), the form-induced production represents the work that the local Reynolds stresses perform against local gradients due to spatial velocity variations.

#### 2.5. Budget equation for the WKE components

Similarly, it is possible to formulate budget equations for the dispersive normal stresses. Again, no summation over index  $\alpha = 1, 2, 3$  is intended if one wishes to obtain the budgets for the three individual components of the WKE, separately. To ensure a clear distinction from terms of the TKE budget, we add the superscript  $\sim$  to terms of the WKE budget, such that

$$\frac{\partial}{\partial t} \left\langle \frac{1}{2} \widetilde{\overline{u}}_{\alpha} \widetilde{\overline{u}}_{\alpha} \right\rangle = \underbrace{-\left\langle \widetilde{\overline{u}}_{\alpha} \widetilde{\overline{u}}_{j} \right\rangle \frac{\partial \langle \overline{u}_{\alpha} \rangle}{\partial x_{j}} + \left\langle \widetilde{\overline{u}_{\alpha} u_{j}'} \frac{\partial \widetilde{\overline{u}}_{\alpha}}{\partial x_{j}} \right\rangle + \left\langle \overline{u_{\alpha}' u_{j}'} \right\rangle \left\langle \frac{\partial \widetilde{\overline{u}}_{\alpha}}{\partial x_{j}} \right\rangle}_{\text{production} (\Pi_{shear}^{\sim} - \Pi_{wake} - \Pi_{mean})} \\ \underbrace{-\frac{1}{2} \frac{1}{\theta} \frac{\partial \theta}{\partial x_{j}} \left\langle \widetilde{\overline{u}}_{\alpha} \widetilde{\overline{u}}_{\alpha} \widetilde{\overline{u}}_{j} \right\rangle}_{\text{transport} (T_{disp}^{\sim} + T_{turb}^{\sim})} - \frac{1}{\theta} \frac{\partial \theta}{\partial x_{j}} \left\langle \widetilde{\overline{u}}_{\alpha} \widetilde{\overline{u}_{\alpha}} u_{j}' \right\rangle}_{(\text{pseudo-) dissipation } (\epsilon^{\sim})} \\ + \frac{1}{\rho} \left\langle \widetilde{\overline{p}} \frac{\partial \widetilde{\overline{u}}_{\alpha}}{\partial x_{\alpha}} \right\rangle - \frac{1}{\rho} \left\langle \frac{\partial \widetilde{\overline{u}}_{\alpha} \widetilde{\overline{p}}}{\partial x_{\alpha}} \right\rangle + \nu \left\langle \frac{1}{2} \frac{\partial^{2} \widetilde{\overline{u}}_{\alpha} \widetilde{\overline{u}}_{\alpha}}{\partial x_{j} \partial x_{j}} \right\rangle = 0. \quad (2.11)$$

redistribution  $(R^{\sim})$  mixed role (equations (2.12) and (2.13))

The first term on the right-hand side of (2.11) represents a shear production mechanism, as dispersive shear stresses act against the bed-normal gradient of the double-averaged flow velocity. The second and third terms resemble the wake and mean production, respectively, which we summarise as form-induced production. Compared with (2.9), the terms appear here with opposite sign. The fourth and fifth terms are responsible for dispersive and turbulent transport in bed-normal direction, as the terms can only have non-zero values for j = 3. The sixth and seventh terms are identified as dissipation and inter-component redistribution of spatial variance, respectively. The last two terms on the right-hand side of (2.11) remind of pressure diffusion and viscous transport. A mere interpretation as transport terms, however, would neglect the non-zero boundary terms  $BT_{\alpha}(\tilde{u}_{\alpha}\tilde{p})/\rho$  and  $BT_j(v \tilde{u}_{\alpha} \partial \tilde{u}_{\alpha}/\partial x_j)$ . These boundary terms could be interpreted as transport of  $\tilde{u}_{\alpha} \tilde{u}_{\alpha}$  across the fluid-solid interface, which is formally possible as both  $\tilde{u}_{\alpha}$  and  $\langle \bar{u}_{\alpha} \rangle$  violate the no-slip boundary condition. Knowing that the boundary term represents an integral along the intersection curve s of the averaging plane with the solid sphere surfaces (see (2.6)), we can substitute  $\tilde{u}_{\alpha} = -\langle \bar{u}_{\alpha} \rangle$  due to the no-slip boundary condition on the sphere

Journal of Fluid Mechanics



Figure 1. Introduction of spatial variance to the flow field by exclusively viscous interaction on the surface of a very thin plate with flow-parallel orientation. The sketch shows a top view of the averaging plane (x-y-plane).

surfaces, and we obtain

$$-\frac{1}{\rho}\left\langle\frac{\partial\overline{\widetilde{u}}_{\alpha}\overline{\widetilde{p}}}{\partial x_{\alpha}}\right\rangle = \underbrace{-\frac{1}{\rho}\frac{1}{\theta}\frac{\partial\theta\langle\overline{\widetilde{w}}\,\overline{\widetilde{p}}\rangle}{\partial z}}_{\rho}\underbrace{-\frac{1}{\rho}\langle\overline{u}_{\alpha}\rangle BT_{\alpha}(-\overline{\widetilde{p}})}_{\rho},\tag{2.12}$$

$$\nu \left\langle \frac{1}{2} \frac{\partial^{2} \widetilde{\overline{u}}_{\alpha} \widetilde{\overline{u}}_{\alpha}}{\partial x_{j} \partial x_{j}} \right\rangle = \underbrace{\nu \frac{1}{2} \frac{1}{\theta} \frac{\partial \theta \left\langle \frac{\partial \widetilde{\overline{u}}_{\alpha} \widetilde{\overline{u}}_{\alpha}}{\partial z} \right\rangle}{\operatorname{transport}(T_{visc}^{\sim})}}_{\operatorname{transport}(T_{visc}^{\sim})} \underbrace{- \langle \overline{u}_{\alpha} \rangle BT_{j} \left( \nu \frac{\partial \widetilde{\overline{u}}_{\alpha}}{\partial x_{j}} \right)}_{\operatorname{production}(\overline{\Pi_{v,BT}^{\sim}})}.$$
(2.13)

The formulation in (2.12) and (2.13) isolates exclusive bed-normal transport terms  $T_{orres}^{2}$ and  $T_{visc}^{\sim}$  from fluxes across the fluid solid interface, which appear as the production terms  $\Pi_{n-BT}^{\sim}$  and  $\Pi_{n-BT}^{\sim}$ . The formulation suggests that spatial variance is generated as the double-averaged bed-parallel velocities work against the pressure drag and the part of the viscous drag that results from in-plane velocity variations. For the pressure drag, it can be shown that  $BT_{\alpha}(\overline{p}) = BT_{\alpha}(\overline{p})$  for  $\alpha = 1, 2$ , such that it makes no practical difference whether  $\langle \overline{p} \rangle$  is included if  $\langle \overline{w} \rangle = 0$ . However, it appears plausible that the viscous drag component  $\langle \overline{u}_{\alpha} \rangle BT_i(\partial \langle \overline{u}_{\alpha} \rangle / \partial x_i)$  does not contribute to the production of WKE, as otherwise, spatial variances would also be spuriously introduced into the flow over a horizontal and smooth surface. Whereas WKE production due to pressure drag is well documented (e.g. Raupach & Shaw 1982), the WKE production due to viscous interaction with solid surfaces is often neglected in budget formulations (e.g. Raupach & Shaw 1982; Yuan & Piomelli 2014; Ghodke & Apte 2016; Hantsis & Piomelli 2020). The fact that viscous surface interactions can lead to spatial variance in an otherwise undisturbed velocity field is illustrated by figure 1, where boundary layers form on both sides of a very thin plate, which pierces the x-y-averaging plane. From a mathematical perspective, the decomposition in (2.13) ensures that the viscous transport  $T_{visc}$  is free of net sources, which is an important property of a transport term.

#### 2.6. Budget equation for the MKE

From multiplying (2.7) with  $\langle \overline{u} \rangle$ , we obtain the MKE budget equation for the streamwise velocity component, which completes the set of budget equations. This equation reads



Figure 2. Energy transfer pathways between MKE, WKE and TKE. The arrows indicate the direction of energy flow when the corresponding terms have a positive value. Sources by volume forces, losses by dissipation and vertical transport are not depicted.

$$\frac{\partial}{\partial t} \left( \frac{1}{2} \langle \overline{u} \rangle \langle \overline{u} \rangle \right) = \underbrace{\langle \overline{u'w'} \rangle}_{\text{production } (-\Pi_{shear} - \Pi_{shear}^{\sim})} \underbrace{\frac{\partial \langle \overline{u} \rangle}{\partial z}}_{\text{production } (-\Pi_{shear} - \Pi_{shear}^{\sim})} \underbrace{\frac{\partial}{\partial z}}_{\text{viscous term } (T_{visc} + \epsilon)} \underbrace{\frac{-\frac{1}{\theta}}{\frac{\partial \theta}{\sqrt{u'w'}} \langle \overline{u} \rangle}_{\text{transport } (T_{disp} + T_{turb})}}_{\text{transport } (T_{disp} + T_{turb})} \underbrace{\frac{+\frac{1}{\theta}}{\frac{\partial \overline{u}}{\sqrt{u'w'}} \langle \overline{u} \rangle}_{\text{source } (S)}}_{\text{action against total drag}} = 0.$$

$$(2.14)$$

The first and second terms on the right-hand side of (2.14) resemble the shear production terms, which appear in (2.9) and (2.11) with the opposite sign. The third term, labelled 'viscous term', summarises viscous transport and viscous dissipation, whereas we refrain from a lengthy reformulation of the term, which introduces multiple boundary terms. The fourth and fifth terms can be identified as transport terms. The driving volume force  $g_x$  acts as a source of MKE in the sixth term. Altogether, terms seven to nine represent the work of the double-averaged streamwise flow field against the drag. Knowing that  $BT_1(\tilde{p}) = BT_1(\bar{p})$ , we detect that the seventh and eighth term appear here with opposite signs as in (2.12) and (2.13), which is not the case for the ninth term.

#### 2.7. Energy transfer mechanisms

We conclude the theory part by summarising all transfer mechanisms between TKE, WKE and MKE, which are identified by means of terms that appear with opposite signs in the budget equations. Figure 2 visualises the energy transfer pathways between the budgets. The arrows indicate the direction of energy transfer if the corresponding terms have positive values. Transport terms, dissipative losses of WKE and TKE, as well as energy input into the MKE budget due to the volume force are not shown explicitly. According to the energy transfer pathways, shear production mechanisms can generate TKE or WKE at the expense of MKE. Additionally, WKE can result from the work of the double-averaged



Figure 3. Properties of the sediment bed. (a) In-plane porosity profiles of different realisations of the sphere pack. The interface z = 0 is defined where  $\frac{\partial^2 \theta}{\partial z^2} = 0$ . The porosity profiles are aligned according to the interface position. (b) Spatial autocorrelation of the bed elevation fluctuation  $\tilde{z}_b$  over the horizontal shift r for different realisations.

flow field against the pressure drag and the part of the viscous drag, which is caused by spatial velocity variations. Finally, form-induced production can transfer WKE into TKE and *vice versa*.

# 3. Methodology

We have simulated turbulent open-channel flow over mono-disperse random sphere packs (v.Wenczowski & Manhart 2024). In the case configuration, the sphere pack approximates the sediment bed of a gravel bed river, whereas the spheres play the role of sediment grains and remain static during the flow simulation. By fully resolving the pore space, we allow the flow to enter the pore space. The bottom domain boundary intersects the sphere pack. A free-slip condition ensures that momentum is only transferred to the sphere surfaces and not at the bottom wall, which thus reduces the influence of the bottom domain boundary. On the surface of the spheres, a no-slip boundary condition is specified. At the top domain boundary, a free-slip condition is used to approximate a free water surface. In the streamwise *x*-direction and lateral *y*-direction, periodic domain boundary conditions are set. A constant volume force in streamwise direction emulates the effect of gravity in a sloped channel. In the statistically stationary state, the flow depth *h* equals the thickness  $\delta$  of the fully developed boundary layer.

# 3.1. Representation of the porous medium

Mono-disperse random sphere packs of different extents were generated as described by v.Wenczowski & Manhart (2024). The generation process is conducted such that a level mean bed surface results. Exemplarily, figure 3(a) shows the in-plane porosity profiles  $\theta(z)$  of five different realisations of the bed used in the M-cases, which has a base area of  $A_0 = 64D \times 32D$ . The collapse of porosity profiles for different realisations indicates that the generation mechanism avoids strongly unique features. The inflection point  $\partial^2 \theta / \partial z^2 = 0$  of the porosity profile is used as a geometric interface definition, which is consistent with Voermans *et al.* (2017). The distance from the geometrically determined interface to the top domain boundary defines the different flow depths *h*, whereas the sediment bed has a thickness of 5D in all simulated cases. The local bed elevation  $z_b$  is obtained by defining a vertical line at position (x, y). The height of the topmost intersection point between this line and the surface of the sediment grains yields  $z_b(x, y)$ . The variable  $\tilde{z}_b$  represents the fluctuation of the bed elevation field around its mean value. Figure 3(b) describes



Figure 4. Overview of the dimensionless parameter space, including reference points from the literature. The grey dashed lines represent fixed ratios between the flow depth h (i.e. boundary layer thickness) and the sphere diameter D. As reference points, we refer to Breugem *et al.* (2006), Voermans *et al.* (2017), Shen *et al.* (2020) and Karra *et al.* (2023). Figure adapted from v.Wenczowski & Manhart (2024).

the bed surface by means of the spatial autocorrelation of  $\tilde{z}_b$ . A fast decay of the spatial autocorrelation function indicates that no repeating patterns are present in the bed surface.

# 3.2. Parameter space

Various Reynolds numbers can be used to characterise the flow conditions in different regions of the domain (e.g. Voermans et al. 2017). We choose the friction Reynolds number  $Re_{\tau}$  and permeability Reynolds number  $Re_{K}$  as the primary parameters to span a two-dimensional parameter space. The friction Reynolds number  $Re_{\tau} = u_{\tau}h/v$ is well-established in channel flow investigations and describes the unconfined flow above the sediment layer. In contrast, the permeability Reynolds number  $Re_K = u_\tau \sqrt{K}/v$ characterises the interface of the porous medium. Both Reynolds numbers consider the friction velocity  $u_{\tau}$ , which we compute via a balance of forces as  $u_{\tau} = \sqrt{g_x h}$ . The permeability Reynolds number uses the square root of the sediment permeability K as a length scale, which can be conceptually understood as an effective pore diameter (Breugem et al. 2006). According to the Kozeny–Carman equation (Kozeny 1927; Carman 1937),  $\sqrt{K}$  is proportional to the sphere diameter D. Relating this length scale to the viscous sublayer length scale,  $Re_K$  describes if the smallest scales of turbulent motion can penetrate into the pore space. Accordingly,  $Re_K \ll 1$  and  $Re_K \gg 1$  indicate effectively impermeable and highly permeable boundaries, respectively, whereas  $Re_K \approx 1-2$  is identified as a transition between both extremes (Voermans et al. 2017). A variation of h/D, i.e. the ratio of the flow depth to the sphere diameter, allows us to investigate different combinations of  $Re_{\tau}$  and  $Re_{K}$ . High values of h/D up to 10 were chosen to mitigate the blocking effect introduced by individual spheres. By considering  $Re_{\tau} > 150$ , we aim to reduce low-Reynolds-number effects, whereas the upper bound of  $Re_{\tau} = 500$  is dictated by computational affordability. The chosen range of  $Re_K = 0.4 - 2.8$  includes the transition region around  $Re_K \approx 1-2$ . In summary, figure 4 visualises the eight sampling points in terms of  $Re_{\tau}$  and  $Re_{K}$  that we probe in this study. Table 1 contains further parameters describing the simulated cases. Among those parameters,  $k_s^+$  deserves special attention, as it allows us to categorise case S-150 as transitionally rough. With  $k_s^+ \approx$ 50 - 60, cases M-150 and S-300 lie near the onset of the fully rough regime (e.g. Kadivar et al. 2021), while the remaining cases lie within the fully rough regime. As described

Case	h/D	$L_x/h \times L_y/h$	$\Delta x^+_{i,min}$	$\Delta x^+_{i,max}$	$D^+$	$Re_{\tau}$	$Re_K$	$Re_b$	Rep	$k_s^+$
L-180	3	$13.3 \times 6.7$	0.94	0.94	58	174	1.63	1232	0.95	131
L-300	3	$13.3 \times 6.7$	1.04	2.08	100	300	2.82	2114	2.77	204
M-150	5	$12.8 \times 6.4$	0.63	2.52	31	154	0.87	1305	0.15	59
M-300	5	$12.8 \times 6.4$	0.63	2.52	60	300	1.69	2444	0.59	126
M-500	5	$12.8 \times 6.4$	1.04	4.16	100	500	2.82	4075	1.60	202
S-150	10	$12.8 \times 6.4$	0.31	1.24	15	150	0.42	1714	0.02	16
S-300	10	$12.8 \times 6.4$	0.63	2.52	30	300	0.84	3105	0.07	50
S-500	10	$12.8 \times 6.4$	1.04	4.16	50	500	1.40	5037	0.20	95
I-180	$\rightarrow \infty$	$13.3 \times 6.7$	0.63	1.26	0	180	0	2718	0	0
I-300	$\rightarrow \infty$	$12.8 \times 6.4$	0.75	3.00	0	300	0	5034	0	0
I-500	$\rightarrow \infty$	$12.8 \times 6.4$	0.90	3.60	0	500	0	9027	0	0

Table 1. Overview of dimensionless parameters. The variable *D* represents the sphere diameter, *h* is the flow depth, *L* is the extent of the domain,  $\Delta x_{i,min}^+$  provides the side length of the smallest cubic cells near the interface and  $\Delta x_{i,max}^+$  specifies the side length of the largest cells in the free-flow region. Friction, permeability, bulk, particle and roughness Reynolds numbers are defined as  $Re_{\tau} = u_{\tau}h/v$ ,  $Re_K = u_{\tau}\sqrt{K}/v$ ,  $Re_b = u_bh/v$ ,  $Re_p = \langle \overline{u} \rangle^s D/v$  and  $k_s^+ = u_{\tau}k_s/v$ . Further, *K* is the permeability,  $u_{\tau}$  represents the shear velocity,  $u_b$  is the bulk velocity and  $k_s$  is the equivalent sand-grain roughness height.



Figure 5. Roughness quantification in dependence of  $Re_K$ . (a) Shift  $\Delta u^+$  of the velocity profile in comparison to flow over a smooth wall at comparable  $Re_\tau$ . (b) Corresponding roughness Reynolds number  $k_s^+$ , computed from  $\Delta u^+$  via the relation given on the y-axis (Jiménez 2004), where  $\kappa = 0.4$  is used for the von Kármán constant.

in v.Wenczowski & Manhart (2024), the values of  $k_s^+$  were determined from the velocity shift  $\Delta u^+$  in relation to a smooth-wall flow case at comparable  $Re_{\tau}$ . The smooth-wall cases I-180, I-300, and I-500 are formally characterised by  $h/D \rightarrow \infty$ . Figure 5 shows both the velocity shift  $\Delta u^+$  and  $k_s^+$  in dependence of  $Re_K$ .

#### 3.3. Interface definition

The nominal parameters of the simulation cases refer to an interface position, which is purely geometrically defined by the inflection point of the porosity profile. In v.Wenczowski & Manhart (2024), we observed that the drag distribution on the porous medium exhibits a characteristic peak near the sediment–water interface, which marks the region where momentum from the free flow region is absorbed. The features of this characteristic peak were used to describe the interface region. The centroid of the drag distribution was associated with the mean interface position  $\mu_z$ , whereas the spread  $\sigma_z$ was found to provide a useful proxy for an interfacial length scale.



Figure 6. Interface parameters derived from the distribution of drag on the porous medium, as described in v.Wenczowski & Manhart (2024). The mean interface position  $\mu_z$  reflects the drag maximum, whereas  $\sigma_z$  quantifies the spread of the drag distribution. *D* represents the sphere diameter.

Figure 6 shows the interface parameters  $\mu_z$  and  $\sigma_z$  in dependency of  $Re_K$ . Whereas the drag-based interface  $\mu_z$  moves to lower positions with increasing  $Re_K$ , the spread  $\sigma_z/D$  only varies slightly over the  $Re_K$ -range. In the scope of the present study, positions will be quantified in z/D, where the vertical coordinate z refers to the geometrically defined interface and D is the sphere diameter. Wherever appropriate, we will add the grey dashed line from figure 6(a) to provide the position  $\mu_z$  as a reference.

# 3.4. Numerical methods

The flow fields were obtained by DNS, for which our in-house code MGLET (Manhart, Tremblay & Friedrich 2001; Manhart 2004; Peller *et al.* 2006; Sakai *et al.* 2019) was employed. MGLET solves the conservation laws for mass (2.1) and momentum (2.2) by an energy-conserving central second-order finite volume method. A Cartesian grid with staggered arrangement of variables is used with local grid refinement in a multi-level approach (Manhart 2004). An explicit third-order low-storage Runge–Kutta method (Williamson 1980) with a fractional step formulation (Chorin 1967) advances the solution in time. The required pressure update defines an elliptic problem, which is solved efficiently by a multi-level Poisson solver. The geometry of the pore space is resolved by a ghost-cell immersed boundary method, in which a second-order spatial interpolation (Peller *et al.* 2006; Peller 2010). In Appendix B, we describe the implemented ghost-cell immersed boundary method in detail and show the convergence behaviour of different terms accompanied by a comparison to a body-fitted mesh.

#### 3.5. Accuracy assessment

The convergence of the flow simulation for a random sphere pack was demonstrated in v.Wenczowski & Manhart (2024), yielding that 48 cells per diameter are sufficient to obtain an accurate representation of the permeability. Further, a reasonable agreement of the double-averaged velocity profile and the turbulent and dispersive stresses with experimental data of Voermans *et al.* (2017) has been observed. It was also demonstrated that the near-interface spatial resolution of  $\Delta x_{i,min}^+ \approx 1.0$  allows an adequate resolution of all turbulent length scales in this region. Statistics were collected over a time T with  $T u_{\tau}/h \in [27, 39]$ .

An evaluation of all terms in the budgets of TKE and WKE allows us to check the closure of the budgets. For the TKE budgets, the largest amplitude of the residual is observed near  $z/D \approx 0$ . The residual is smaller than 3 % of the amplitude of the production peak, which is found at a similar height. In most cases, a positive sign of the residual



Figure 7. Near-interface profiles of TKE and WKE, normalised by the friction velocity  $u_{\tau}$ . The vertical coordinate *z* refers to the geometrically defined interface and is normalised by the sphere diameter *D*.

indicates that we may slightly underpredict the dissipation. In comparison to the TKE, more effort is required to achieve good closure of the WKE budget. Though we exploit the second-order accuracy of the immersed boundary implementation, spikes in the resulting profiles of the term  $\Pi_{\nu-BT}^{\sim}$  near the sphere crests did not vanish. A test with a single sphere (not shown here) allowed us to connect those spikes to the thin viscous boundary layers forming at the crests of individual protruding spheres. For a cleaner graphical representation, however, those spikes were removed by smoothing the profiles with a Gaussian kernel. The smoothed profile for the term  $\Pi_{\nu-BT}^{\sim}$  keeps the residual in the MKE budget below 4.2 % of the production peak.

# 4. Results

In this section, we will first describe the distribution of MKE, WKE and TKE, before we present the budgets for the latter two components of the kinetic energy. Double-averaged profiles as well as the spatial distributions of the kinetic energy components are presented in § 4.1 and § 4.2, respectively. In § 4.3, we investigate the outer-layer behaviour of TKE budget terms, before we focus exclusively on the near-interface region. We discuss one representative near-interface TKE budget in detail (§ 4.4), show the scaling behaviour of source and sink terms (§ 4.5), and decompose the transport into individual processes (§ 4.6). The same analysis steps are repeated for the WKE, such that we start with the near-interface budget (§ 4.7), proceed to the scaling behaviour of sources and sinks (§ 4.8), and finish with a detailed look at the transport (§ 4.9).

# 4.1. Near-interface profiles of TKE and WKE

As a basis for the discussion of the kinetic energy budgets, figure 7 shows the near-interface profiles of plane-averaged TKE and WKE. The profiles are normalised by  $u_{\tau}$  and plotted against z/D.

For all simulated cases, the TKE attains peak values above the interface, and quickly decays near and below the interface. Above their peaks near  $z/D \approx 1$ , the TKE profiles group according to the ratio h/D under the given normalisation. A cross-comparison between profiles suggests that both increasing  $Re_{\tau}$  and increasing  $Re_{K}$  contribute to higher intensities of velocity fluctuation at z/D = 0. For case S-150, which is associated with the transitionally rough regime, an emphasised peak in the TKE distribution is found at  $z/D \approx 1.2$ , which is above the peak location of other profiles. This qualitative difference of the transitionally rough case S-150 can be explained by the turbulence structure of the buffer layer including streaks and quasi-streamwise vortices, which vanish at higher  $Re_K$  (v.Wenczowski & Manhart 2024). The WKE profiles reach their maxima at  $z/D \approx$ 0.2–0.5. There is a trend towards higher peaks at lower locations with increasing  $Re_K$ . Directly above the peak, the WKE decreases rapidly towards the free flow region, such that only small amounts of WKE remain above  $z/D \approx 1$ . Most profiles behave similarly in the region of  $z/D \in [0.5, 1]$  near the crests of the topmost spheres, which hints at a direct influence of the bed geometry on the distribution of the WKE. According to the layer concept of Nikora *et al.* (2001), which is based on a horizontal-averaging perspective, the nearly complete decay of dispersive stresses at  $z/D \approx 1.2 - 1.5$  marks the upper end of the form-induced sublayer and, thus, also the upper end of the roughness layer. Below z = 0, the WKE profiles group well visibly according to  $Re_K$ . With increasing  $Re_K$ , the spatial velocity variations entrain into progressively deeper regions of the sediment. Again, the transitionally rough case S-150 renders an exception, as the amplitude of the WKE peak is smaller and the peak is found at a higher position. This observation can be explained by the rather strong wall-blocking effect at  $Re_K \approx 0.4$ , which allows stable recirculation vortices to occupy gaps between the topmost spheres, such that the downstream spheres are sheltered from the approaching flow (v.Wenczowski & Manhart 2024).

#### 4.2. Spatial distribution of TKE and WKE

To facilitate the interpretation of the previous profiles, we consider the spatial distributions of  $\overline{u'_{i}u'_{i}}/2$  and  $\overline{\tilde{u}}_{j}\overline{\tilde{u}}_{j}/2$ , i.e. the distribution of the kinetic energies prior to the horizontal averaging operation. Figure 8 visualises the different quantities within a vertical slice through the domain of case M-300. The largest values of the TKE are found slightly above the sediment crests. Between the sediment crests and  $z/D \approx 1.5$ , individual spots of increased TKE are recognisable. The TKE appears to be more homogeneously distributed at larger elevations, suggesting that the influence of spatial inhomogeneities in the sediment bed, such as individual protruding spheres, is limited to a confined region. High values of the WKE are found only in direct proximity of the sediment bed surface. In particular, the wake regions behind the crests of prominently protruding spheres induce strong deviations from the plane-averaged velocity, as shown by the inset in figure 8(b). These regions are likely to be responsible for the peak in the WKE profile, which would also explain the rapid decrease of WKE above the crests of the topmost spheres. The noslip boundary condition dictates that  $\overline{u}_i = 0$  on the sphere surface, which implies that  $\overline{u}_i = 0$  $-\langle \overline{u}_i \rangle$ . Accordingly, the WKE is generally not zero on the surface of the spheres, but has a local value of  $\langle \overline{u}_i \rangle \langle \overline{u}_i \rangle / 2$ , which corresponds to the MKE at the respective z-position. As a result, thin layers of large WKE are also found on the wind-ward side of exposed spheres.

# 4.3. Outer-layer similarity of TKE budget terms

In v.Wenczowski & Manhart (2024), we observed an outer-layer similarity among the TKE profiles of cases with comparable  $Re_{\tau}$ . While the TKE profiles far from the sediment surface remained similar across different h/D or  $Re_K$ , a near-wall TKE peak was damped



Figure 8. Spatial distribution of TKE and WKE within an arbitrarily chosen x-z-plane of simulation case M-300. The values are normalised by the square of the friction velocity  $u_{\tau}$ . Coordinates in the x- and z-directions are given in x/D and z/D, respectively, where D is the sphere diameter.

with increasing  $Re_K$ . That motivates us to investigate the TKE budgets in an outer scaling with the flow depth h and the friction velocity  $u_\tau$ . Figure 9 shows the budgets in terms of total production, total transport and dissipation according to (2.9). The profiles are plotted over the complete flow depth, while cases with similar  $Re_\tau$  are shown in one plot. The region far from the surface of the sediment bed is characterised by a collapse of the curves for similar  $Re_\tau$ , which suggests an outer-layer similarity of the budget terms. Slightly above the sediment–water interface, the TKE budget terms depend strongly on  $Re_K$ . Smooth-wall cases and cases with a low permeability Reynolds number show an emphasised production peak in this region, which flattens out with progressively higher  $Re_K$ . As the influence of roughness and permeability seems to be most emphasised in the near-interface region, we will focus on this region in a deeper analysis of the budget.

# 4.4. Overview of the near-interface TKE budget

To obtain a comprehensive image of all processes involved, we analyse the near-interface TKE budget of the case M-300. With  $Re_{\tau} = 300$  and  $Re_K \approx 1.7$ , case M-300 lies approximately in the centre of our parameter space and, thus, provides a representative example. Figure 10(*a*) shows the TKE budget normalised with the friction velocity  $u_{\tau}$  and the sphere diameter *D*, which provides a typical length scale in the interface region. Whereas transport processes are summarised in the total transport  $T_{tot}$ , the individual contributions of shear and form-induced production are plotted separately. The total production peaks at  $z/D \approx 0.5$ , whereas the dissipation rate  $\epsilon$  at the same position is smaller. A larger share of the TKE which is produced but not dissipated appears to be transported downwards into the pore space of the porous medium. In the region below  $z/D \approx -0.1$ , more TKE is provided by the transport than by the production. With increasing depth, the TKE input from transport is nearly exclusively balanced by the dissipation  $\epsilon$ . The major part of the TKE production peak. In comparison to that, the



Figure 9. TKE budget terms in outer scaling. Total production ( $\Pi_{tot}$ , ---), total transport ( $T_{tot}$ , ----) and dissipation ( $\epsilon$ , ——) are normalised by the flow depth h and the friction velocity  $u_{\tau}$ . Plots show groups of cases with similar  $Re_{\tau}$ , but different  $Re_{K}$ .

contribution of form-induced production appears to be minor, except in the region below z/D = -0.3, where hardly any shear production takes place.

Figure 10(*b*–*d*) provides the budgets for individual components of the TKE. Nearly the complete TKE is produced in the component  $\langle \overline{u'u'} \rangle$ . Approximately half of the produced  $\langle \overline{u'u'} \rangle$  is dissipated, whereas the rest is redistributed to  $\langle \overline{v'v'} \rangle$  and  $\langle \overline{w'w'} \rangle$  by the pressure redistribution  $P_{redist}$ . The pressure-based inter-component redistribution is the main source of bed-normal velocity fluctuations, and reaches its largest positive contribution in the budget of  $\langle \overline{w'w'} \rangle$  at  $z/D \approx 0.5$ . Compared with other terms involved, vertical transport plays a major role in the budget of  $\langle \overline{w'w'} \rangle$ . Below a depth of  $z/D \lesssim -0.2$ , the pressure-based redistribution term in the budget of  $\langle \overline{w'w'} \rangle$  changes its sign, such that TKE is distributed back to the other components. The detail in figure 10(*b*) shows that this intercomponent redistribution even acts as a source of streamwise velocity fluctuations in the region z/D < -0.3.

# 4.5. Scaling of TKE sources and sinks

In what follows, we investigate how the maxima of the production and dissipation and their locations depend on the Reynolds numbers. The left column, i.e. figure 11(*a*), shows the maximal values normalised with  $u_{\tau}^3/D$  over  $Re_K$ . Figure 11(*b*) shows the elevations at which the maximum intensity of the respective process is observed. We also added as a reference the position of the centroid of the drag distribution  $\mu_z$ , which can be used as an interface position (see § 3.3). The normalised total TKE production increases with  $Re_K$ , but seems to saturate once the hydraulically fully rough regime is reached ( $k_s^+ \gtrsim 70$  at  $Re_K \gtrsim 1$ ). Following the trend of  $\mu_z$ , the location of the total production peak lowers



Figure 10. Budgets for the complete TKE and for the individual Reynolds normal stresses in the near-interface region. Case M-300 serves as an example. For normalisation, the shear velocity  $u_{\tau}$  and the sphere diameter *D* are used. The vertical coordinate *z* refers to the geometrically defined interface and is normalised by *D*. Note that the horizontal axes cover different value ranges.

in the range of  $Re_K < 1.5$ , but seems to stabilise at  $z/D \approx 0.5$  for  $Re_K > 1.5$ . Both in terms of magnitude and position, the peaks of the shear production  $\Pi_{shear}$  appear to go in line with the peaks of total production, as the shear production is the main TKE production mechanism (compare figure 10). The data points of cases L-300 and M-500, however, indicate that higher  $Re_K$  may also slightly reduce the shear production. Starting from nearly zero-value at  $Re_K = 0.42$ , the maximal value of the form-induced production  $\Pi_{form}$  increases monotonously with increasing  $Re_K$ . In comparison to  $\Pi_{shear}$ , however, the form-induced production plays a secondary role. Even at  $Re_K \approx 2.8$ , the maximum



Figure 11. Scaling of production terms and dissipation of TKE with  $Re_K$ . (a) Maxima of the processes normalised by the friction velocity  $u_{\tau}$  and the sphere diameter D. (b) Vertical position of the maxima with respect to the geometrically defined interface, whereas z is normalised by D. The grey dashed line represents the position  $\mu_z$  of the drag-based interface (v.Wenczowski & Manhart 2024). The total production  $\Pi_{tot}$  summarises the shear production  $\Pi_{shear}$  and the form-induced production  $\Pi_{form}$ .  $\epsilon$  represents the dissipation.

value of form-induced production is approximately a fourth of the maximal value of shear production. The peak of the form-induced production is found near  $z = \mu_z$  and, thus, at a lower position than the shear production peak. By means of an instantaneous field, figure 12 illustrates the nature of the form-induced production mechanism. The wake regions behind individual spheres seem to have major contributions. Horseshoe-like vortices, which form on the windward side of exposed spheres, can equally lead to a positive form-induced production. The observation that form-induced production acts on small spatial scales comparable to the grain scale is likely to explain the smaller peak value of  $\Pi_{form}$ . The maximal amplitude of the dissipation is lower than the maximal values of production, as the dissipation takes place over a wider vertical region than the production. With increasing  $Re_K$ , the maximal dissipation values still grow slightly. The dissipation maxima are also found at a lower elevation than the total production maxima, which results from increasing vertical TKE transport into the negative *z*-direction.

The observations in figure 11 suggest that the permeability Reynolds number  $Re_K$  has decisive impact on the TKE sources and sinks in the interface region, whereas an influence **1014** A 17-20



Figure 12. Instantaneous field of the form-induced TKE production mechanism. The shear velocity  $u_{\tau}$  and the sphere diameter *D* are used for normalisation. The shown patch is a fraction of the domain of case M-300. Coordinates are given as x/D and y/D, respectively.

of  $Re_{\tau}$  is hardly noticeable. With larger  $Re_K$ , the maxima of different processes move to progressively lower elevations, thus following the drag-based interface (grey dashed lines in figure 11). For  $Re_K \leq 3$ , shear production remains the dominant production process. In § 5, we discuss the behaviour of the dominant shear production in detail and show how its distribution is linked to the interface position and the interfacial length scale.

#### 4.6. TKE transport and fluxes

In the following, we focus on the TKE transport in the region near the sediment-water interface. The total vertical transport  $T_{tot}$  is decomposed into contributions of the specific transport processes  $T_{proc}$ , representing turbulent transport, pressure diffusion, viscous transport and dispersive transport, respectively. Under normalisation with  $u_{\tau}$  and D, figure 13(*a*) shows the individual transport budget terms  $T_{proc}$  for case M-300. In addition, figure 13(*b*) provides the superficially averaged vertical TKE fluxes  $J_{proc}^s$  associated with the individual processes. The relation between both quantities is given as

$$T_{proc} = -\frac{1}{\theta} \frac{\partial \theta J_{proc}}{\partial z} = -\frac{1}{\theta} \frac{\partial J_{proc}^s}{\partial z} \quad . \tag{4.1}$$

For case M-300, TKE is transported upwards above  $z/D \approx 0.7$  and downwards below this position, as indicated by a positive flux above and a negative flux below this point. A similar TKE flux upwards into the free-flow region was documented by Raupach *et al.* (1991) and Mignot *et al.* (2009). In the direct proximity of the interface, viscous and dispersive transport cause downward-oriented TKE fluxes of small amplitude. The downward orientation of the dispersive flux contrasts the observations of Shen *et al.* (2020), who report upward dispersive transport. The turbulent transport  $T_{turb}$  has a dominant contribution to the removal of TKE from the region near the sphere crests, where the production maximum is found. A large share of the TKE is transported upwards into



Figure 13. Individual transport terms in the TKE budget and the corresponding superficially averaged TKE fluxes. Case M-300 serves as an example. The shear velocity  $u_{\tau}$  and the sphere diameter D are used for normalisation. The vertical coordinate z refers to the geometrically defined interface and is normalised by D.

the free-flow region. Below  $z/D \approx 0.7$ , a negative turbulent flux transports TKE deeper into the sediment bed.

In contrast to the other TKE transport processes, pressure transport can only cause net vertical transport of  $\langle \overline{w'w'} \rangle$ . Even above the crests of the topmost spheres at z/D > 1, the corresponding flux has a negative sign, which implies that pressure transport transfers TKE from the free flow region towards and into the sediment bed. At  $z/D \approx 0.6$ , further TKE is picked up, such that the downwards-oriented flux reaches its maximum amplitude at approximately z/D = 0.2. Deeper below the interface at z/D < -0.5, pressure transport introduces more TKE than other transport processes. The efficient propagation of vertical velocity fluctuation into deeper sediment layers is likely explained by a superposition of both small-scale pressure fluctuations originating from the interface region and large-scale pressure fluctuations from the free flow region. Under normalisation with the cube of the friction velocity, figure 14 shows the maximal amplitudes of the downward-oriented TKE flux due to pressure transport. Among cases with similar  $Re_K$ , the cases with the largest ratio h/D exhibit the largest value of max( $|J_{pres}^{s}|)/u_{\tau}^{3}$ . In the fully rough regime, the smaller relative roughness for cases with large h/D results in a larger bulk velocity  $u_b$ , which seems to increase the TKE flux. Also under normalisation with  $u_h^3$  (not shown here), the flux maxima do not collapse, which supports the idea that effects of free-flow and nearinterface scales are superposed. Except for case S-150, the vertical position of the largest downward-oriented TKE flux, which corresponds to the zero-crossing of the budget term, coincides approximately with the drag-based interface position  $\mu_z$ .

#### 4.7. Overview of the near-interface WKE budget

In the following, we focus on the WKE budget, which gives us detailed insight into the production, transport and destruction of spatial variance in the time-averaged velocity field. Again, we use case M-300 as an exemplary case for the detailed analysis.



Figure 14. Amplitude of the downward-oriented TKE flux due to pressure transport over the permeability Reynolds number  $Re_K$ . (a) Maximal amplitude of the TKE flux due to pressure transport, normalised by the friction velocity  $u_{\tau}^3$ . (b) Vertical position of the maximum with respect to the geometrically defined interface, whereas z is normalised by D. The grey dashed line represents the position  $\mu_z$  of the drag-based interface.

Figure 15(*a*) shows the budget of the total WKE. The total production  $\Pi_{tot}^{\sim}$  peaks at  $z/D \approx 0.3$ . From this production maximum, WKE is transported in both directions. Small amounts of WKE are moved in the positive z-direction, such that the total transport  $T_{tot}^{\sim}$  has a positive contribution at  $z/D \approx 1$ . The majority of the WKE, however, is relocated into deeper regions of the sediment bed, where the transport constitutes the only positive budget term. Similar to the TKE budget, the maximal dissipation of WKE also takes place slightly below the peak of the WKE production. The total production  $\Pi_{tot}^{\sim}$  summarises the shear production  $\Pi_{shear}^{\sim}$ , the form-induced production  $\Pi_{form}^{\sim} = -\Pi_{form}$  and the WKE production that results from interaction with the sphere surfaces via the pressure ( $\Pi_{p-BT}^{\sim}$ ) and via viscous stresses ( $\Pi_{\nu-BT}^{\sim}$ ). The form-induced production transfers kinetic energy from the WKE to the TKE and, therefore, appears with a negative sign in the WKE budget. In comparison to the shear production, a larger share of WKE production results from the interactions with the sphere surfaces is not considerably smaller than the production due to pressure-based surface interactions.

To complete the picture, figure 15(*b*–*d*) shows the budgets for the individual WKE components. All four production mechanisms are involved in the budget of  $\langle \tilde{u} \, \tilde{u} \rangle$ . Approximately half of the produced variations in the streamwise velocity field are dissipated in the region near the production peak at  $z/D \approx 0.3$ . A considerable part of the excessively produced WKE is transferred to  $\langle \tilde{v} \, \tilde{v} \rangle$  and  $\langle \tilde{w} \, \tilde{w} \rangle$ . The redistributed WKE constitutes the only term with a major positive contribution in the budget of  $\langle \tilde{v} \, \tilde{v} \rangle$ . The negative sign of the form production term indicates that spatial variations in the lateral velocity field are reduced, while temporal fluctuations  $\langle v'v' \rangle$  are generated. Transport processes play a critical role in the budget of  $\langle \tilde{w} \, \tilde{w} \rangle$ . Above the interface at  $z/D \approx 0.25$ , inter-component redistribution increases variations in the bed-normal velocity field, whereas only a small amount of these variations is dissipated. While only a small amount is transported upwards, most of the excessively introduced  $\langle \tilde{w} \, \tilde{w} \rangle$  is transported downwards into the sediment bed. In those deeper regions, the redistribution mechanism  $R^{\sim}$  acts in the opposite direction, as it takes WKE out of  $\langle \tilde{w} \, \tilde{w} \rangle$  and introduces it even back into  $\langle \tilde{u} \, \tilde{u} \rangle$ , as shown by the detail in figure 15(*b*).

# 4.8. Scaling of WKE sources and sinks

Figure 15 has shown that shear production by dispersive stresses  $\Pi_{shear}^{\sim}$ , as well as  $\Pi_{p-BT}^{\sim}$  and  $\Pi_{v-BT}^{\sim}$  produce WKE in the interface region. Besides the dissipation, the form-induced



Figure 15. Budgets for the complete WKE and for the individual dispersive normal stresses in the nearinterface region. Case M-300 serves as an example. For normalisation, the shear velocity  $u_{\tau}$  and the sphere diameter *D* are used. The vertical coordinate *z* refers to the geometrically defined interface and is normalised by *D*. Note that the horizontal axes cover different value ranges.

production of TKE acts as a sink of WKE. Figure 16(a) shows the maximal values of different WKE sources and sinks, which are plotted over  $Re_K$ . The values are normalised by the friction velocity  $u_{\tau}$  and the sphere diameter D. Figure 16(b) provides the elevations at which the maxima are found.

For  $Re_K \leq 1$ , the maximum of the total production becomes larger with increasing  $Re_K$ , whereas its value seems to saturate in the region of  $Re_K > 1$ . With increasing  $Re_K$ , the maximum value of WKE shear production increases monotonically. For the transitionally rough case S-150, dispersive shear stresses are very small, such that hardly any shear production is observed. The shear production maximum is found at progressively lower



Figure 16. Scaling of production mechanisms and dissipation of WKE with  $Re_K$ . (a) Maximal values of the processes normalised with the friction velocity  $u_\tau$  and the sphere diameter D. (b) Position of the maxima with respect to the geometrically defined interface, whereas the vertical coordinate z is normalised by D. The grey dashed line represents the position  $\mu_z$  of the drag-based interface. The total production  $\Pi_{tot}^{\sim}$  summarises the processes  $\Pi_{shear}^{\sim}, \Pi_{p-BT}^{\sim}$  and  $\Pi_{\nu-BT}^{\sim}$ , whereas  $\epsilon^{\sim}$  is the dissipation.

heights with increasing  $Re_K$ . For all simulated cases,  $\Pi_{p-BT}^{\sim}$ , i.e. the WKE production due to work of the double-averaged flow field against the pressure drag, exceeds the shear production, while it also increases monotonously with increasing  $Re_K$ . The maximum of  $\Pi_{p-BT}^{\sim}$  is found at approximately the same vertical position as the maximal shear production. The production  $\Pi_{v-BT}^{\sim}$ , which results from the work of the double-averaged flow field against the viscous drag from in-plane velocity variations, decreases slightly with increasing  $Re_K$ . For the transitionally rough case S-150, the maximum of  $\Pi_{v-BT}^{\sim}$  is higher than the maximum of  $\Pi_{p-BT}^{\sim}$ , indicating an important role of viscous effects. With



Figure 17. Individual transport terms in the WKE budget and the corresponding superficially averaged WKE fluxes. Case M-300 serves as an example. The shear velocity  $u_{\tau}$  and the sphere diameter D are used for normalisation. The vertical coordinate z refers to the geometrically defined interface and is normalised by D.

increasing  $Re_K$ , the relative importance of  $\prod_{v-BT}^{\sim}$  in comparison to other WKE production mechanisms declines but remains noticeable. The maximum of  $\prod_{v-BT}^{\sim}$  is found near the crests of the topmost spheres and thus at a greater elevation than the maxima of other processes. For all cases, the maximum value of the dissipation is smaller than that of the total production of WKE, while figure 15 indicates that dissipation takes place over a wider region. With increasing  $Re_K$ , the form-induced production of TKE (figure 11) also removes progressively larger amounts of WKE. The dissipation maximum is found at approximately the same elevation as the maximum of the total production. As already observed for the TKE, the maxima of the WKE sources and sinks move to lower vertical positions with increasing  $Re_K$ . Thus, they follow a trend in the equally  $Re_K$ -dependent position  $\mu_z$  of the drag-based interface, which is marked by a grey dashed line in figure 16.

#### 4.9. WKE transport and fluxes

As done for the TKE in §4.6, we continue with a detailed discussion of the processspecific transport terms  $T_{proc}^{\sim}$  in the WKE budget, which are shown in figure 17(*a*). The corresponding superficially double-averaged WKE fluxes  $J_{proc}^{\sim s}$  are provided in figure 17(*b*), and the relation between both quantities is given by (4.1). The total transport moves a large part of the WKE from the region near  $z/D \approx 0.3$ . As shown by the large amplitude of the negative flux around z/D = 0, WKE is predominantly transported downwards. Only turbulent transport seems to transfer a small amount of spatial velocity variations into the region z/D > 1, where the WKE is small, but not absolutely zero. Viscous and dispersive transport cause comparatively smaller fluxes  $J_{visc}^{\sim s}$  and  $J_{disp}^{\sim s}$ , which relocate WKE only in direct proximity of the interface, whereas they neither affect the free flow region nor greater depths of the sediment bed. Compared with turbulent transport, pressure transport causes a similarly strong downwards oriented WKE flux  $J_{pres}^{\sim s}$  from the interface region. The flux from pressure transport, however, peaks at a lower position and also introduces spatial velocity variations into greater depths of z/D < -1. In contrast to



Figure 18. Amplitude of the downward-oriented WKE flux due to pressure transport over the permeability Reynolds number  $Re_K$ . (a) Maximal amplitude of the WKE flux due to pressure transport, normalised by the friction velocity  $u_t^3$ . (b) Vertical position of the maxima with respect to the geometrically defined interface, whereas z is normalised by D. The grey dashed line represents the position  $\mu_z$  of the drag-based interface.

that, the pressure transport hardly introduces any spatial velocity variations in the free flow region.

Vertical pressure-driven transport propagates WKE into deeper regions of the sediment and acts via spatial variations of  $\overline{w}$ , which makes the process also highly relevant for dispersive mass transport in the hyporheic zone. That motivates us to investigate the scaling behaviour of the flux  $J_{pres}^{\sim s}$  in detail. As shown by figure 18, the maximal amplitude of the downward oriented flux is reached slightly below  $z = \mu_z$  and it follows the dragbased interface. When the maximal amplitude of the downward-oriented flux is normalised by  $u_{\tau}^{2}$  and plotted over  $Re_{K}$ , we observe a nonlinear increase, such that a clearly interpretable scaling behaviour cannot be deduced. To find an appropriate scaling, an idealised scenario of pressure pumping is sketched in Appendix C, and different terms are evaluated analytically. The analytic solutions suggest that  $J_{pres}^{\sim s}$  scales with  $(K/\nu\rho^2)\hat{p}^2k_x$ , where  $\hat{p}$  represents the amplitude of a regular pressure variation at the interface, while  $k_x$  is the wavenumber of the regular pressure variation. According to the Kozeny–Carman equation, the permeability K scales with  $D^2$ . Further, we assume that  $\hat{p}$  is proportional to  $\rho u_{\tau}^2$  and that  $k_x$  is proportional to 1/D. These assumptions suggest a scaling of  $J_{pres}^{\sim s}$ with  $u_{\tau}^4 D/v$ . Figure 18 shows that, under normalisation with  $u_{\tau}^4 D/v$ , the highest value of  $J_{pres}^{\sim s}$  is reached for cases with  $Re_K \approx 1$ , whereas it decreases monotonically for higher  $Re_K > 1$ . Again, no interpretable scaling behaviour can be observed. Elliott & Brooks (1997) propose a scaling of the pressure variations with the bulk velocity, which similarly does not seem to apply for our cases without macroscopic bed forms (not shown here). In  $\S5$ , we discuss a potential scaling of the pressure-driven processes in the near-interface region, which includes the roughness-induced dimensionless velocity shift  $\Delta u^+$  as an additional parameter.

#### 5. Discussion

Finnigan (2000) stated that work against the viscous component of the canopy drag leads to a direct dissipation of MKE into heat. Revisiting the budget equations, however, we

encounter a term which represents an energy transfer from MKE to WKE via viscous interaction between the flow and the solid surfaces. While the term results formally from a rigorous application of the rules for spatial derivatives within the horizontal averaging framework (e.g. Giménez-Curto & Lera 1996), we can also find a simple example, which intuitively illustrates the existence of such a viscosity-based WKE production mechanism (see figure 1). As the studies of Yuan & Piomelli (2014) or Ghodke & Apte (2018) do not explicitly mention WKE production via viscous interaction with solid surfaces, the question remains if this process is relevant in the context of turbulent flow over a random sphere pack.

For flow over a random sphere pack at  $Re_K < 3$ , our results suggest a clear 'yes'. For the transitionally rough case S-150, viscous- and pressure-based surface interactions contribute to the WKE production in approximately equal parts. In contrast, the shear production of WKE is negligible for case S-150, which can be explained by the strong wall-blocking and the very low dispersive shear stresses near the interface (v.Wenczowski & Manhart 2024). Even for the cases L-300 and M-500 with  $Re_K \approx 2.8$ , the relative contribution of the WKE production due to viscous surface interaction does not become negligible, though it is smaller than the dominant WKE production due to pressure drag. Accordingly, the shift in the relative impact of the production mechanism reflects the transition of the roughness regime (Raupach *et al.* 1991; Jiménez 2004; Kadivar *et al.* 2021) from the transitionally rough to the fully rough regime. An extrapolation of this trend could explain that in atmospheric flow (e.g Raupach & Shaw 1982), the WKE production via viscous interaction could be neglected for extreme roughness and permeability, which is not generally justified for hyporheic flow problems.

With increasing  $Re_K$ , the form-induced production converts progressively larger amounts of WKE into TKE. Even for the fully rough cases in this study, however, the form production remains small in comparison to the shear production of TKE, which appears to be the dominant process in the near-interface TKE budget. This observation agrees with the findings of Fang *et al.* (2018) and Shen *et al.* (2020). The investigation of an instantaneous field showed that form-induced production takes place within a thin layer near the sediment bed surface and occurs on small scales, which are comparable to the sphere diameter. As stated by Finnigan (2000), the introduction of TKE on smaller length scales explains why wake production is less efficient than shear production.

In the present study, we used the inflection point of the porosity profile as a geometrical interface definition and the sphere diameter D as an interface length scale. Within this reference frame, the maxima of production and dissipation terms are found at progressively lower positions with increasing  $Re_K$ . In v.Wenczowski & Manhart (2024), we proposed a drag-based interface description, where the height  $\mu_z$  represents the position of maximal momentum absorption near the interface and  $\sigma_z$  quantifies the spread of the region in which the momentum is absorbed. We used  $\mu_z$  to define the interface position and a consistent friction velocity was computed as  $u_\tau^{\mu} = \sqrt{g_x(h - \mu_z)}$ . Together with  $\sigma_z$ , an interface coordinate was defined as  $\gamma = (z - \mu_z)/\sigma_z$ . In the following, we deviate from the geometric interface definition and discuss the scaling behaviour of the shear production in the drag-based framework.

Figure 19 shows that  $\partial \langle \overline{u} \rangle / \partial z$  scales with  $u_{\tau}^{\mu} / \sigma_z$ , which means that a momentum absorption over a wider region reduces the shear intensity. Further, the figure shows that Reynolds shear stress  $\langle u'w' \rangle^s$  scales approximately, though not perfectly, with  $(u_{\tau}^{\mu})^2$ . Together, both observations explain the scaling behaviour of the shear production term with  $(u_{\tau}^{\mu})^3 / \sigma_z$ , i.e. with quantities that are characteristic for the interface region. Only the shear production profile of the transitionally rough case S-150 deviates strongly from



Figure 19. Near-interface profiles of the shear intensity, the Reynolds shear stress and the resulting shear production of TKE. The vertical coordinate  $\gamma$  considers the drag-based interface position at  $z = \mu_z$  and uses the spread  $\sigma_z$  of the drag distribution as a length scale. The friction velocity  $u_\tau^{\mu}$  is consistent with the drag-based interface at  $z = \mu_z$ .

the profiles of the remaining hydraulically rough cases, which collapse reasonably well when plotted against  $\gamma$ . In combination with the observed trend that the maximum values of other processes of the TKE budget similarly follow the drag-based interface position (figure 11), the similarity of the shear production distribution further underlines the flow-dynamical relevance of this interface definition.

The similarity of the profiles suggests that the TKE shear production scales with interface-related length and velocity scales. In outer scaling with  $u_{\tau}$  and h, this observation explains why the near-interface TKE production peak flattens out with progressively larger  $Re_K$ . Far from the interface, however, the TKE budget terms of cases with similar  $Re_{\tau}$  show a good similarity in outer scaling (see figure 9). This co-existence of two differently scaling regions indicates that these regions hardly influence each other. The notion of a certain, yet by far not complete, separation between a near-interface region and an outer layer is supported by the observation of a layer at  $z/h \approx 0.4$ , where dissipation and production budget terms are in equilibrium, whereas transport terms hardly play a role.

Within the horizontal double-averaging framework, the pressure diffusion in bednormal direction only acts via the vertical velocity component w. In contrast to other transport processes, pressure-based vertical transport propagates temporal fluctuations or spatial variations of the velocity field into deeper regions of the sediment bed. The interface also seems to be a source region of TKE, which is transported downwards by pressure diffusion. However, we also observe downward-oriented pressure-based transport of temporal velocity fluctuation from the free-flow region. The interface and free-flow region are therefore not entirely decoupled. In contrast to that, pressure diffusion of WKE only acts between the interface region and the sediment bed below. The exclusive dependency on  $Re_K$  is a further indication that the free-flow region is not involved. To discuss the WKE budget terms further, we draw parallels to a simplified two-dimensional scenario, which is sketched in Appendix C. On the surface of a permeable bed, a regular pressure variation characterised by a single wavenumber  $k_x$  is prescribed as a boundary condition and drives the flow field in the porous medium. For this simplified scenario, terms representing pressure-driven mechanisms can be evaluated analytically. The analytic solution predicts that the amplitude of the downward oriented flux of  $\langle \widetilde{\overline{w}} \ \widetilde{\overline{w}} \rangle$  is largest at



Figure 20. (a,b) Near-interface profiles of WKE redistribution terms and (c) of the pressure transport term. The vertical coordinate  $\gamma$  considers the drag-based interface position at  $z = \mu_z$  and uses the spread  $\sigma_z$  of the drag distribution as a length scale. The friction velocity  $u_\tau^{\mu}$  is consistent with the drag-based interface at  $z = \mu_z$ . The dimensionless velocity shift  $\Delta u^+$  includes the effect of roughness.

the surface of the permeable bed, where the driving pressure field is applied as a boundary condition. In agreement with that, our simulations show that the maximal amplitude of the flux  $J_{pres}^{\sim s} = \theta \langle \widetilde{pw} \rangle$  is found only slightly below the drag-based interface at  $z = \mu_z$ . Also, the analytical solution agrees with the observation that the pressure-diffusion mechanism acts as a source for vertical velocity variations in deeper regions of the sediment bed (figure 17). Beyond that, a pressure redistribution from the vertical velocity variation to the bed-parallel velocity variation is predicted by the analytical solution, which we also see in the simulations at greater depths (figure 15). These points indicate that the behaviour of the budget terms in deeper regions represents a pressure pumping scenario, which agrees with the observation of Shen *et al.* (2022) for irregular rough surfaces. In the near-interface region, this pumping scenario is superposed by other processes, which are not captured by the simplified scenario with an unresolved interface region. Among those processes is the near-interface pressure redistribution from  $\langle \widetilde{u} \ \widetilde{u} \rangle$  towards  $\langle \widetilde{v} \ \widetilde{v} \rangle$  and  $\langle \widetilde{w} \ \widetilde{w} \rangle$ . This finding emphasises the role of the topmost sediment layer, which was highlighted by Karra *et al.* (2023).

The amount of WKE, which is transferred into  $\langle \widetilde{w} \ \widetilde{w} \rangle$  and transported downwards, is neither proportional to  $u_{\tau}^3$  nor to  $u_{\tau}^4$  (figure 18), such that we assume that it is necessary to include information about the roughness into a potential scaling relation. In figure 20, the profiles of pressure redistribution and pressure transport terms are plotted against the drag-based interface coordinate  $\gamma$ . For the normalisation, we use  $(u_{\tau}^{\mu})^3 \Delta u^+ / \sigma_z$ , where  $u_{\tau}^{\mu}$  represents the interface-adapted friction velocity and  $\sigma_z$  acts as an interfacial length scale. The dimensionless parameter  $\Delta u^+$  represents the shift of the dimensionless velocity profile with respect to the smooth-wall flow case at comparable  $Re_{\tau}$  (figure 5). Accordingly, the value of  $\Delta u^+$  can be seen as a robust proxy for the cumulative impact of the roughness. The similarities among the normalised profiles indicate that the amount of WKE that is transferred into  $\langle \widetilde{w} \ \widetilde{w} \rangle$  and transported into deeper regions scales well with  $(u_{\tau}^{\mu})^3 \Delta u^+ / \sigma_z$  in both the transitionally rough and the fully rough regime. As shown in figure 5,  $\Delta u^+$  increases monotonically, but nonlinearly, with  $Re_K$ .

1014 A17-30

# 6. Conclusions

Based on previously validated data from pore-resolved direct numerical simulations, we evaluated the double-averaged budgets of both turbulent kinetic energy (TKE) and wake kinetic energy (WKE) for turbulent flows over mono-disperse random sphere packs. Eight cases were analysed and act as sampling points within a parameter space, which is spanned by friction Reynolds numbers  $Re_{\tau} \in [150, 500]$  and permeability Reynolds numbers  $Re_{K} \in [0.4, 2.8]$ . Varying ratios of flow depth to sphere diameter of  $h/D \in \{3, 5, 10\}$  allowed an investigation of cross-combination between both Reynolds numbers. With roughness Reynolds numbers of  $k_{s}^{+} \in [20, 200]$ , the simulated cases can be categorised as transitionally rough or hydraulically fully rough. The underlying data sets have been validated in v.Wenczowski & Manhart (2024), such that the present study could focus exclusively on the budget evaluations, for which we achieve full closure with residuals of less than approximately 4% of the locally largest term in the budget. For a representative case in the centre of our parameter space, the complete budgets of TKE and WKE were exemplary shown and discussed in detail. Further, we evaluated scaling of different processes with  $Re_{K}$  and  $Re_{\tau}$ .

We demonstrated that viscous interactions between the flow and the solid sphere surfaces can transfer kinetic energy of the double-averaged flow field into WKE, thus contributing to an increased spatial variance of the time-averaged flow field. To our knowledge, this transfer process has not yet been investigated in detail for turbulent flow over porous media, whereas a similar mechanism based on the pressure drag is well documented. For a transitionally rough case, half of the near-interface WKE production results from viscous interactions at the sphere surfaces. With progressively higher permeability and roughness, the relative influence of the viscous interaction decreases compared with the pressure interaction. However, it remains non-negligible throughout the parameter space of the present study. In contrast to atmospheric sciences, these findings suggest that WKE production due to viscous surface interactions cannot be considered negligible in the hyporheic region.

With increasing roughness and permeability, the form-induced production gains importance and transfers progressively larger amounts of WKE into TKE. Despite this trend, mainly shear production is responsible for a characteristic TKE production peak in the near-interface region. Our data suggest that the near-interface production peak of TKE scales with the friction velocity and an interface-related length scale, such as the spread of the drag distribution. In the region far from the sediment bed, however, the TKE budget terms of cases with similar  $Re_{\tau}$  showed a high degree of similarity under outer-scaling with the friction velocity and the flow depth. Among different transport processes of TKE and WKE, the pressure diffusion appears most effective in propagating temporal fluctuations and spatial velocity variations into greater depth of the sediment bed. Whereas the analysis of TKE fluxes indicates that temporal velocity variations can also have their origin in the free flow region, WKE is transferred downwards from the sediment-water interface. The amount of WKE which is propagated into deeper layers of the porous medium via vertical velocity variations scales well with the friction velocity and a roughness parameter. A redistribution of WKE takes place in greater depth and resembles the behaviour observed in an idealised pressure pumping scenario.

Without doubt, the analysis of TKE budgets advances our mechanistic understanding of processes within the hyporheic zone. Particularly for  $Re_K = O(1)$ , however, the WKE budget deserves similar attention, as spatial variations in the time-averaged flow play a decisive role in the dispersive transport of mass and momentum across the interface.

Acknowledgements. We gratefully acknowledge the correspondence with Joey Voermans and Marco Ghisalberti, as well as discussions with Yoshiyuki Sakai, Lukas Unglehrt and Rainer Helmig. In particular, we would like to mention the contribution of Alexander McCluskey who unfortunately passed away too early.

**Funding.** The authors gratefully acknowledge the financial support of the DFG under grant no. MA2062/15-1. Computing time was granted by the Leibniz Supercomputing Centre on SuperMUC-NG (project "pn68vo").

Declaration of interests. The authors report no conflict of interest.

Author contributions. Simulations and postprocessing were performed by S. V. Wenczowski. Both authors contributed to reaching conclusions and writing the paper.

#### Appendix A. Formulation of the dissipation term

The full-dissipation formulation of the budget equations for TKE and WKE builds on the following notation of the Navier–Stokes equation:

$$\frac{\partial u_i}{\partial t} + u_j \frac{\partial u_i}{\partial x_j} = -\frac{1}{\rho} \frac{\partial p}{\partial x_i} + \frac{\partial \tau_{ij}}{\partial x_j} + g_i , \quad \text{where} \quad \tau_{ij} = 2\nu S_{ij} = \nu \left( \frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} \right)$$
(A1)

In (A1),  $S_{ij}$  represents the strain rate tensor. In the double-averaged momentum equation, the shear rate tensor appears in the viscous transport term as well as by the viscous drag term, which leads us to

$$\frac{\partial \langle \overline{u}_{\alpha} \rangle}{\partial t} = \frac{1}{\theta} \frac{\partial}{\partial x_{j}} \left( \underbrace{\frac{\partial \langle \overline{u}_{\alpha} \rangle}{\partial x_{j}} + \frac{\partial \langle \overline{u}_{j} \rangle}{\partial x_{\alpha}}}_{visc.} \underbrace{\frac{\partial \langle \overline{u}_{\alpha} u_{j}' \rangle}{turb.}}_{f_{p,\alpha}} \underbrace{\frac{\partial \langle \overline{u}_{\alpha} u_{j}' \rangle}{\partial x_{\alpha}}}_{f_{\nu,\alpha}} \underbrace{\frac{\partial \langle \overline{u}_{\alpha} u_{j}' \rangle}{\partial x_{\alpha}}}_{f_{\nu,\alpha}} \underbrace{\frac{\partial \langle \overline{u}_{\alpha} u_{j}' \rangle}{\partial x_{\alpha}}}_{f_{\nu,\alpha}} \underbrace{\frac{\partial \langle \overline{u}_{\alpha} u_{j}' \rangle}{\partial x_{\alpha}}}_{(A2)}$$

The obtained (A2) is consistent with the formulation chosen by Lian *et al.* (2021). In the budget equation of TKE and WKE, the full dissipation terms appear as

$$\epsilon_{full} = -\nu \left\langle \frac{\partial u'_{\alpha}}{\partial x_j} \frac{\partial u'_{\alpha}}{\partial x_j} + \frac{\partial u'_{\alpha}}{\partial x_j} \frac{\partial u'_j}{\partial x_{\alpha}} \right\rangle = \epsilon - \nu \left\langle \frac{\partial u'_{\alpha}}{\partial x_j} \frac{\partial u'_j}{\partial x_{\alpha}} \right\rangle \tag{A3}$$

and

$$\epsilon_{full}^{\sim} = -\nu \left\langle \frac{\partial \widetilde{u}_{\alpha}}{\partial x_j} \frac{\partial \widetilde{u}_{\alpha}}{\partial x_j} + \frac{\partial \widetilde{u}_{\alpha}}{\partial x_j} \frac{\partial \widetilde{u}_j}{\partial x_{\alpha}} \right\rangle = \epsilon^{\sim} - \nu \left\langle \frac{\partial \widetilde{u}_{\alpha}}{\partial x_j} \frac{\partial \widetilde{u}_j}{\partial x_{\alpha}} \right\rangle.$$
(A4)

By the example of case M-300, figure 21 shows that the differences between pseudo dissipation and full dissipation are minor. For the TKE budget, this observation agrees with the statement of Pope (2000). Additionally, the small differences indicate that a pseudo dissipation formulation of the WKE budget is also justifiable.

#### Appendix B. Immersed boundary implementation

As pressure and viscous drag need to be evaluated, the method and accuracy of the immersed boundary implementation in MGLET deserve attention. Instead of feedback-forcing with a distributed forcing field (e.g. Goldstein, Handler & Sirovich 1993), MGLET relies on a direct-forcing method, which comprises three steps within each

# **1014** A17-32



Figure 21. Minor differences between full dissipation and pseudo dissipation for both (a) TKE and (b) WKE. Case M-300 was used as an example. The friction velocity  $u_{\tau}$  and the sphere diameter D are used for normalisation.

Runge–Kutta substep (Peller 2010; Sakai & Manhart 2020): (i) in an interpolation step, a stencil formulation is used to determine the velocities in cells intersected by solid surfaces. Under consideration of the velocities in neighbouring fluid-filled cells, the velocity in an intersected cell is computed such that the Dirichlet boundary condition at the position of the solid surface is fulfilled; (ii) in the flux correction step, the mass fluxes through the open faces of the intersected cell are computed. To ensure mass conservation at the immersed boundary, the divergence of the velocity field within the intersected cell is distributed among the neighbouring cells based on the open areas between the cells. That ensures that the rotation of the velocity field remains unchanged; (iii) the third step is the solution of a Poisson equation for the fluid-filled cells, which yields a pressure correction required to obtain a divergence-free flow field. As the velocity in the fluid-filled cells is updated, the fluxes through the faces of the intersected cell also change, such that steps (ii) and (iii) are iterated until the whole flow field is divergence-free. Only then, the next Runge-Kutta substep is entered.

We checked the solution of the pressure field around the immersed boundary for laminar flow around a cylinder by comparing it with a highly resolved simulation with a body-fitted finite volume method in OpenFOAM (Weller et al. 1998). Figure 22 shows the pressure fields for various grid resolutions. The flow within the periodic domain is driven by a volume force  $g_x$ . Even at coarser resolutions, the immersed boundary yields a pressure field, which appears free of artificial distortions and visually similar to the solution on a body-fitted mesh. As the Poisson equation is only solved for the fluid-filled cells, no pressure values are available for the intersected cells in the immersed boundary case (best seen in figure 22c). The pressure drag of the cylinder, which we evaluate as  $f_{p, IBM} = \langle \partial \overline{p} / \partial x \rangle$ , converges with first-order accuracy, as shown by figure 23. The values of  $f_{p,IBM}$  at resolutions of 48 or more cells per diameter only deviate from the value  $f_{p, BF}$  of the body-fitted simulation by less than 0.7 %. The value  $f_{p, BF}$  is obtained by integrating (p n) over the cylinder surface, where n is the normal vector. Also, the value of the viscous drag  $f_{\nu,IBM} = \mu \langle \partial / \partial x_j (\partial \overline{u} / \partial x_j) \rangle$  agrees well with  $f_{\nu,BF}$ , which we obtain by computing the wall shear stress and integrating it over the cylinder surface of the body-fitted simulation. The values of  $f_{v,IBM}$  shown in figure 23(b) converge monotonically, whereas a convergence order cannot be specified.

# S. v. Wenczowski and M. Manhart



Figure 22. Pressure fields for laminar flow around cylinder in a two-dimensional x-y-periodic domain. Results from immersed boundary method at different resolutions are compared with computation on a body-fitted mesh.



Figure 23. Convergence study of pressure and viscous drag determined by the immersed boundary method. The result from a simulation with a body-fitted mesh is given for comparison. The side length  $\Delta x$  of the cubic cells is normalised by the cylinder diameter *D*. The drag is normalised by  $(g_x V_f)$ , where  $g_x$  is the driving volume force and  $V_f$  is the fluid volume. Accordingly, both normalised drags sum to unity.

# Appendix C. Pressure pumping scenario

We consider the following two-dimensional scenario, which resembles the case discussed by Elliott & Brooks (1997). The surface of a sediment bed with a permeability K and a depth  $h_b$  lies at z = 0. On the sediment bed surface, a pressure field is prescribed as

$$p(x, z=0) = \hat{p} \cos(k_x x) = \hat{p} \frac{1}{2} \left( e^{ik_x x} + e^{-ik_x x} \right),$$
(C1)

1014 A17-34



Figure 24. Qualitative visualisation of the analytical solution and normalised profiles of different terms. The analytical solution in panel (*a*) shows contour lines of the pressure field. The black arrows represent the flow from high pressure (red) to low pressure (blue). The budget terms in panel (*b*) represent the pressure redistribution term and the pressure transport term in the budget for  $\partial/\partial t \langle \widetilde{w} \ \widetilde{w} \rangle/2$ . The flux term in panel (*c*) represents the pressure-driven downward flux of  $\langle \widetilde{w} \ \widetilde{w} \rangle/2$ . The permeability *K*, the dynamic viscosity  $\mu$ , the amplitude  $\hat{p}$  and the wavenumber  $k_x$  of the interfacial pressure variation are used for normalisation.

where  $\hat{p} > 0$  is the amplitude of the regular cosine-shaped pressure variation and  $k_x = 2\pi/\lambda_x$  is the angular wavenumber of the regular spatial pressure variation with wavelength  $\lambda_x$ . For the interfacial boundary condition of (C1), an analytical solution for the pressure and flow field within the porous medium can be found, which fulfils Laplace's equation for the pressure, while also  $w_D(z = -h_b) = 0$  is maintained, which corresponds to the bottom boundary of our simulation cases. Using solutions known in the context of Airy's wave theory in combination with Darcy's law, we obtain

$$p(x, z) = \hat{p} \cos(k_x x) \frac{\cosh(k_x (z+h_b))}{\cosh(k_x h_b)},$$
(C2)

$$u_D(x, z) = -\frac{K}{\mu} \frac{\partial p}{\partial x} = \frac{K}{\mu} k_x \hat{p} \sin(k_x x) \frac{\cosh(k_x (z+h_b))}{\cosh(k_x h_b)},$$
(C3)

$$w_D(x,z) = -\frac{K}{\mu}\frac{\partial p}{\partial z} = -\frac{K}{\mu}k_x \hat{p} \cos(k_x x) \frac{\sinh(k_x(z+h_b))}{\cosh(k_x h_b)}.$$
 (C4)

In (C2), (C3) and (C4),  $\cosh(x) = (e^x + e^{-x})/2$  and  $\sinh(x) = (e^x - e^{-x})/2$  represent the hyperbolic cosine and hyperbolic sine function, respectively. The subscript in  $u_D$ and  $w_D$  identifies the velocity as Darcy velocities, which describe a divergence-free pressure-driven potential flow within the porous medium.

The obtained analytical solution is represented in figure 24(*a*). We use the analytical solution to compute values of terms, which occur in the budget for  $\langle \widetilde{w} \ \widetilde{w} \rangle$ . While no boundary terms occur in the idealised scenario, we obtain profiles for the redistribution term (see (2.11)) and the pressure transport term (see (2.12)). Also, the value of the

pressure-induced WKE flux  $J_{pres}^s = \langle \widetilde{\overline{w}} \ \widetilde{\overline{p}} \rangle$  can be obtained, such that

$$\left\langle \widetilde{\overline{p}} \; \frac{\partial \widetilde{\overline{w}}}{\partial z} \right\rangle = -\left(\frac{K}{\mu} \, \hat{p}^2 k_x^2\right) \left(\frac{\cosh(k_x(z+h_b))}{\cosh(k_x h_b)}\right)^2 \frac{1}{\lambda_x} \int_0^{\lambda_x} \left(\cos(k_x x)\right)^2 dx \tag{C5}$$

$$\left\langle \frac{\partial \overline{w} \, \overline{p}}{\partial z} \right\rangle = -\left(\frac{K}{\mu} \, \hat{p}^2 k_x^2\right) \left( \left(\frac{\cosh(k_x(z+h_b))}{\cosh(k_x h_b)}\right)^2 + \left(\frac{\sinh(k_x(z+h_b))}{\cosh(k_x h_b)}\right)^2 \right) \\ \times \frac{1}{\lambda_x} \int_0^{\lambda_x} \left(\cos(k_x x)\right)^2 \mathrm{d}x$$
 (C6)

$$\left\langle \widetilde{\overline{w}} \, \widetilde{\overline{p}} \right\rangle = -\left(\frac{K}{\mu} \, \hat{p}^2 k_x\right) \frac{\cosh(k_x(z+h_b))}{\cosh(k_x h_b)} \frac{\sinh(k_x(z+h_b))}{\cosh(k_x h_b)} \frac{1}{\lambda_x} \int_0^{\lambda_x} \left(\cos(k_x x)\right)^2 \mathrm{d}x \,. \tag{C7}$$

The expressions in (C5), (C6), (C7) assume that the domain length is a multiple of the wavelength  $\lambda_x$ . Also, the equations show that the flux is expected to scale with  $K \hat{p}^2 k_x/\mu$ , while the budget terms are expected to scale with  $K \hat{p}^2 k_x^2/\mu$ , if the sediment bed depth  $h_b$  does not have a major influence. As shown in figure 24, the normalised quantities approach a zero value with increasing depth. The appearance of  $k_x$  in the z-dependent terms implies that this decay to zero happens closer to the sediment surface if the interfacial pressure variation has a higher wavenumber.

#### REFERENCES

- ANTONIA, R.A. & KROGSTAD, P.-Å. 2001 Turbulence structure in boundary layers over different types of surface roughness. *Fluid Dyn. Res.* 28 (2), 139–157.
- BATTIN, T.J., BESEMER, K., BENGTSSON, M.M., ROMANI, A. & PACKMANN, A.I. 2016 The ecology and biogeochemistry of stream biofilms. *Nat. Rev. Microbiol.* 14 (4), 251–263.
- BOANO, F., HARVEY, J.W., MARION, A., PACKMAN, A.I., REVELLI, R., RIDOLFI, L. & WÖRMAN, A. 2014 Hyporheic flow and transport processes: mechanisms, models, and biogeochemical implications. *Rev. Geophys.* 52 (4), 603–679.
- BREUGEM, W.P., BOERSMA, B.J. & UITTENBOGAARD, R.E. 2006 The influence of wall permeability on turbulent channel flow. J. Fluid Mech. 562, 35–72.
- BRUNKE, M. & GONSER, T. 1997 The ecological significance of exchange processes between rivers and groundwater. *Freshwater Biol.* **37** (1), 1–33.
- CARMAN, P.C. 1937 Fluid flow through granular beds. Chem. Engng Res. Des. 75, 32-48.
- CHORIN, A.J. 1967 The numerical solution of the Navier–Stokes equations for an incompressible fluid. *Bull. Am. Math. Soc.* **73** (6), 928–931.
- ELLIOTT, A.H. & BROOKS, N.H. 1997 Transfer of nonsorbing solutes to a streambed with bed forms: theory. Water Resour. Res. 33 (1), 123–136.
- FANG, H., HAN, X., HE, G. & DEY, S. 2018 Influence of permeable beds on hydraulically macro-rough flow. J. Fluid Mech. 847, 552–590.
- FINNIGAN, J. 2000 Turbulence in plant canopies. Annu. Rev. Fluid Mech. 32 (1), 519-571.
- GHODKE, C.D. & APTE, S.V. 2016 DNS study of particle-bed-turbulence interactions in an oscillatory wallbounded flow. J. Fluid Mech. 792, 232–251.
- GHODKE, C.D. & APTE, S.V. 2018 Roughness effects on the second-order turbulence statistics in oscillatory flows. *Comput. Fluids* 162, 160–170.
- GIMÉNEZ-CURTO, L.A. & LERA, M.A.C. 1996 Oscillating turbulent flow over very rough surfaces. J. Geophys. Res.: Oceans 101 (C9), 20745–20758.
- GOLDSTEIN, D., HANDLER, R. & SIROVICH, L. 1993 Modeling a no-slip flow boundary with an external force field. J. Comput. Phys. 105 (2), 354–366.
- GRANT, S.B., GOMEZ-VELEZ, J.D., GHISALBERTI, M., GUYMER, I., BOANO, F., ROCHE, K. & HARVEY, J. 2020 A one-dimensional model for turbulent mixing in the benthic biolayer of stream and coastal sediments. *Water Resour. Res.* 56 (12), e2019WR026822.

- HAN, X., HE, G. & FANG, H. 2017 Double-averaging analysis of turbulent kinetic energy fluxes and budget based on large-eddy simulation. J. Hydrodyn. 29 (4), 567–574.
- HANTSIS, Z. & PIOMELLI, U. 2020 Roughness effects on scalar transport. Phys. Rev. Fluids 5 (11), 114607.
- JIMÉNEZ, J. 2004 Turbulent flow over rough walls. Annu. Rev. Fluid Mech. 36 (1), 173-196.
- KADIVAR, M., TORMEY, D. & MCGRANAGHAN, G. 2021 A review on turbulent flow over rough surfaces: fundamentals and theories. *Intl J.Thermofluids* 10, 100077.
- KARRA, S.K., APTE, S.V., HE, X. & SCHEIBE, T.D. 2023 Pore-resolved investigation of turbulent open channel flow over a randomly packed permeable sediment bed. *J. Fluid Mech.* 971.
- KOZENY, J. 1927 Ueber kapillare leitung des wassers im boden (in german language). In Sitzungsberichte der Akademie der Wissenschaften Mathematisch-Naturwissenschaftliche Klasse, vol. 136, pp. 271–306.
- KUWATA, Y. & SUGA, K. 2015 Large eddy simulations of pore-scale turbulent flows in porous media by the lattice boltzmann method. *Intl J. Heat Fluid Flow* 55, 143–157, special Issue devoted to the 10th Int. Symposium on Engineering Turbulence Modelling and Measurements (ETMM10) held in Marbella, Spain on September 17-19, 2014.
- KUWATA, Y. & SUGA, K. 2016 Transport mechanism of interface turbulence over porous and rough walls. *Flow Turbul. Combust.* 97 (4), 1071–1093.
- LIAN, Y.P., DALLMANN, J., SONIN, B., ROCHE, K.R., PACKMAN, A.I., LIU, W.K. & WAGNER, G.J. 2021 Double averaging analysis applied to a large eddy simulation of coupled turbulent overlying and porewater flow. *Water Resour. Res.* 57 (11), e2021WR029918.
- MANES, C., POGGI, D. & RIDOLFI, L. 2011 Turbulent boundary layers over permeable walls: scaling and near-wall structure. J. Fluid Mech. 687, 141–170.
- MANHART, M. 2004 A zonal grid algorithm for DNS of turbulent boundary layers. *Comput. Fluids* **33** (3), 435–461.
- MANHART, M., TREMBLAY, F. & FRIEDRICH, R. 2001 MGLET: a parallel code for efficient DNS and LES of complex geometries. In Parallel Computational Fluid Dynamics-Trends and Applications, pp. 449–456.
- MIGNOT, E., BARTHELEMY, E. & HURTHER, D. 2009 Double-averaging analysis and local flow characterization of near-bed turbulence in gravel-bed channel flows. *J. Fluid Mech.* **618**, 279–303.
- NIKORA, V., GORING, D., MCEWAN, I. & GRIFFITHS, G. 2001 Spatially averaged open-channel flow over rough bed. J. Hydraul. Engng 127 (2), 123–133.
- PELLER, N. 2010 Numerische simulation turbulenter strömungen mit immersed boundaries. *Phd thesis*, Technical University of Munich (TUM), Germany.
- PELLER, N., DUC, A.L., TREMBLAY, F. & MANHART, M. 2006 High-order stable interpolations for immersed boundary methods. *Intl J. Numer. Meth. Fluids* 52 (11), 1175–1193.
- PINSON, F., GRÉGOIRE, O. & SIMONIN, O. 2006 k- Macro-scale modeling of turbulence based on a two scale analysis in porous media. *Intl J. Heat Fluid Flow* 27 (5), 955–966, special issue of the 6th International Symposium on Engineering Turbulence Modelling and Measurements – ETMM6.
- POPE, S.B. 2000 Turbulent Flows. Cambridge University Press.
- RAUPACH, M.R., ANTONIA, R.A. & RAJAGOPALAN, S. 1991 Rough-wall turbulent boundary layers. *Appl. Mech. Rev.* 44 (1), 1–25.
- RAUPACH, M.R. & SHAW, R.H. 1982 Averaging procedures for flow within vegetation canopies. *Boundary-Layer Meteorol.* 22 (1), 79–90.
- ROSTI, M.E., CORTELEZZI, L. & QUADRIO, M. 2015 Direct numerical simulation of turbulent channel flow over porous walls. J. Fluid Mech. 784, 396–442.
- SAKAI, Y. & MANHART 2020 Consistent flow structure evolution in accelerating flow through hexagonal sphere pack. *Flow Turbul. Combust.* 105, 581–606.
- SAKAI, Y., MENDEZ, S., STRANDENES, H., OHLERICH, M., PASICHNYK, I., ALLALEN, M. & MANHART, M. 2019 Performance optimisation of the parallel CFD code MGLET across different HPC platforms. In Proceedings of the Platform for Advanced Scientific Computing Conference, PASC '19. Association for Computing Machinery.
- SCHULTZ, M.P. & FLACK, K.A. 2005 Outer layer similarity in fully rough turbulent boundary layers. *Exp. Fluids* **38** (3), 328–340.
- SHEN, G., YUAN, J. & PHANIKUMAR, M.S. 2020 Direct numerical simulations of turbulence and hyporheic mixing near sediment–water interfaces. J. Fluid Mech. 892, A20.
- SHEN, G., YUAN, J. & PHANIKUMAR, M.S. 2022 Quantifying the effects of bed roughness on transit time distributions via direct numerical simulations of turbulent hyporheic exchange. *Water Resour. Res.* 58 (4), e2021WR030503.
- SUGA, K., NAKAGAWA, Y. & KANEDA, M. 2017 Spanwise turbulence structure over permeable walls. J. Fluid Mech. 822, 186–201.
- TOWNSEND, A.A. 1961 Equilibrium layers and wall turbulence. J. Fluid Mech. 11 (1), 97–120.

- VOERMANS, J., GHISALBERTI, M. & IVEY, G. 2017 The variation of flow and turbulence across the sediment– water interface. J. Fluid Mech. 824, 413–437.
- VOERMANS, J., GHISALBERTI, M. & IVEY, G. 2018 A model for mass transport across the sediment-water interface. Water Resour. Res. 54 (4), 2799–2812.
- V. WENCZOWSKI, S. & MANHART, M. 2024 Turbulent flow over random sphere packs an investigation by pore-resolved direct numerical simulation. J. Fluid Mech. 1001, A29.
- WANG, W., YANG, G., EVRIM, C., TERZIS, A., HELMIG, R. & CHU, X. 2021 An assessment of turbulence transportation near regular and random permeable interfaces. *Phys. Fluids* 33 (11), 115103.
- WELLER, H.G., TABOR, G., JASAK, H. & FUREBY, C. 1998 A tensorial approach to computational continuum mechanics using object-oriented techniques. *Comput. Phys.* 12 (6), 620–631.
- WILLIAMSON, J.H. 1980 Low-storage Runge-Kutta schemes. J. Comput. Phys. 35 (1), 48-56.
- WILSON, N. & SHAW, R. 1977 A higher order closure model for canopy flow. J. Appl. Meteorol. 16 (11), 1197–1205.
- YUAN, J. & PIOMELLI, U. 2014 Roughness effects on the Reynolds stress budgets in near-wall turbulence. *J. Fluid Mech.* **760**, R1.